

Connecting via Human Interface Device (HID) Mode


1. Turn on the wireless device on your host (PC, Smartphone, or Tablet).
2. Press the scanner trigger for 1 second to activate the scanner.
3. Scan the [Disconnect] barcode.



4. Press the trigger for 1 second to activate the scanner.
5. Scan the [HID] barcode below:



6. The scanner will emit several short beeps and then stop beeping. The green LED light will flash continually during the pairing process.
7. On your host device, in the settings section where you can see Bluetooth settings and manage your connections.
 - a. You will see the MS910 listed as [Wireless Scanner] under Bluetooth devices.
 - b. You will see a message under that [Pair with this device].
 - c. Select this device on your host and begin to pair.
8. Your Host device will ask you to type in a pin code.
 - a. Use your host device keypad to enter this pin code.
 - b. The pin code can be any set of numbers.
 - c. We suggest using 4 numbers.
9. Once you have entered the pin code on the Host device, you need to set up the pin code on the MS910 to match.
 - a. With the MS910, scan the Pincode Start barcode below.



- b. Refer to the barcode table below, and scan the same numbers that you used as the pin code on your Host device. For example, if your pin code is "241657", scan [2] – [4] – [1] – [6] – [5] – [7] in sequential order:






c. Scan the [Enter] barcode below:



d. Scan the [Pincode-Stop] barcode:



10. On your Host device you will see the message under [Wireless Scanner] saying [connecting...].
11. Once that message turns to [Paired and Connected], the scanner will beep twice to verify a successful connection, and you are ready to start scanning bar code data into your Host device.
 - a. To do a test, open up Word or Note Pad or even a new E-mail [anything that will allow you to type in data].
 - b. Scan a number bar code from this manual.
 - c. That number should appear on your Host device in the application you opened.
 - d. If not, please scan [Disconnect] barcode below and repeat steps 1 to 9 above.

Note. To disconnect the scanner from the host or to switch the wireless profile from one to another, please scan the [Disconnect] barcode:



After scanning the [Disconnect] barcode, the MS910 will emit 3 beeps.

Smartphone Connection (Android)

1. Pair with the scanner via [SPP]; see the topic: *Connecting via Serial Port Profile (SPP) Mode.*

