





Characteristics	Standard	Unit	Result
Type of flooring	ISO 10581-EN 649		Homogeneous Sheet
Material			Polyvinyl chloride
Cover			TRUESHIELD
<b>Safety criteria</b>			
Flammability	GB 8624-2012	class	B1
Flammability	EN 13501-1	class	Bf1
Slip resistance	DIN 51130	group	R9
Dynamic coefficient of friction	EN 13893	class	DS
<b>Performance behaviour</b>			
Sheet width	ISO 24341-EN 426	m	2
Sheet length	ISO 24341-EN 426	m	13-20
Overall thickness	ISO 24346-EN 428	mm	2.0
Total weight	ISO 23997-EN 430	kg/m <sup>2</sup>	2.8
Wear resistance	EN 649	group	T
Binder content	EN ISO10581	Type	Type1
Residual indentation	ISO 24343-1-EN433	mm	0.03
Dimensional stability	ISO 23999-EN 434	-	X :<0.4% Y :<0.4%
Color fastness	ISO 105-B02	rating	≥6
Resistance to staining	EN 423		No Stain 0
<b>Classification</b>			
Domestic	ISO 10874-EN 685	class	23 heavy duty
Commercial	ISO 10874-EN 685	class	34 very heavy duty
Industrial	ISO 10874-EN 685	class	43 heavy duty
<b>Additional property</b>			
Castor Chair  ✓		Antistatic Behaviour  ✓	
Underfloor Heating  ✓		Chemical Resistance  ✓	

REACH

TVOC