



<b>APEX 1290: System Specifications</b>	
<b>Print Speed</b>	Up to 9.14 meters/min (30 ft/min)
<b>Technology</b>	Single Pass 4 Color LED (CMYK)
<b>Printer Processor<sup>1</sup></b>	800/133 MHz
<b>Media Width<sup>2</sup></b>	Minimum: 3.0 inches ( 76.2 mm) Maximum: 12.9 inches (327.7 mm)
<b>Print Width</b>	Minimum: 3.0 inches (76.2 mm) Maximum: 12.6 inches (320 mm)
<b>Print Length</b>	Up to 420 meters (1378 ft)
<b>Substrate Types<sup>3</sup></b>	Die Cut Label Stock Kiss Cut Label Stock Non Die Cut Label Stock Tag Stock
<b>Print Quality</b>	1200 x 600 dpi
<b>Toner Supplies<sup>4</sup></b>	CMY - 16,500 pages @ 5% K - 18,500 pages @ 5% (Rated according to ISO/IEC 19798 guidelines)
<b>Drum Supplies<sup>5</sup></b>	CMYK - 42,000 pages @ 5% (Rated according to ISO/IEC 19798 guidelines)
<b>Feeder System</b>	Input roll maximum outside diameter: 12 inches (305 mm) Core inside diameter: 3 inches (76.2 mm) Maximum input roll weight: 60 lbs (27.2 kg) Cut on the fly, auto cut Auto page width registration Front Panel LCD interface Web management system torque Auto adjusting form synchronization
<b>Rewinder System</b>	Output roll maximum diameter: 12 inches (305 mm) Core inside diameter: 3 inches (76.2 mm) Maximum output roll weight: 60 lbs (27.2 kg)
<b>Dimensions (H X W X D)</b>	Printer & Feeder: 46.3" x 25.7"x24.9" (1177 mm x 654 mm x 633 mm) Rewinder: 16.4" x 19.7" x 21" (415 mm x 500 mm x 533 mm)
<b>Weight</b>	Printer & Feeder: 337.8 lbs (153.2 kg) Rewinder: 30 lbs (13.6 kg)
<b>Operating Environment</b>	Temperature: 10°C to 20°C (50 to 89.6°F) Humidity: 20 to 60% RH
<b>Power</b>	110 - 127 VAC, 50/60 Hz @ 880W 220 - 240 VAC, 50/60 Hz @ 440W
<b>Certifications</b>	FCC Class A, CE, cTUVus, CCC
<b>Warranty</b>	1 year – Parts & Labour
<b>Hard Disk</b>	40 GB internal disk
<b>Memory</b>	512 MB, optional 1GB
<small>1. Published performance results based on laboratory testing. Individual results may vary. 2. Must use Narrow Fuser.</small>	



3. This product is designed and engineered to operate only with genuine iSys Label consumables and certified media substrates. Please contact iSys for the most current Certified Media List of substrates available.
  4. Letter-size sheets at 5% coverage. Printer ships with a 7,500 page set of starter toners.
  5. Based on 500 cut-sheet pages/job.
- iSys Label reserves the right to change product specifications without notice. Trademarks are the property of their respective manufacturers. ©2013 Copyright, iSys Label. All Rights Reserved. All content is subject to change without notice.

<b>APEX 1290: System Requirements</b>	
<b>CPU:</b>	Intel Xeon E5-1650 @ 3.20GHz, or Intel Core i7-3930K @ 3.20GHz
<b>RAM:</b>	12GB RAM (minimum)
<b>HDD:</b>	150GB SATA 10K or 15K RPM
<b>OS:</b>	Windows 7 Professional, or Ultimate 64-bit