



[Click Here to Order](#)

THE
**GOOD
STUFF**

Classic ATF[®]

Kendall[®] Classic ATF is a high-quality transmission fluid recommended for use in all domestic and import vehicles no longer under warranty where the OEM previously specified a GM DEXRON[®]-III H or Ford MERCON[®] fluid.

Classic ATF is formulated to provide the proper frictional characteristics for smooth, quiet shifting in electronically controlled automatic transmissions. It has excellent oxidation resistance for long fluid life, excellent low-temperature properties for easy shifting in cold weather, protects against wear and helps minimize the formation of sludge and varnish.

Applications

- GM and Ford automatic transmissions in 2005 and earlier model-year vehicles that are no longer under warranty, where the OEM previously specified DEXRON[®]-III H, DEXRON[®]-II, DEXRON[®] or MERCON[®] ATF
- Import vehicles where DEXRON[®]-III H⁽¹⁾, or an earlier-generation DEXRON[®] Fluid⁽¹⁾, is specified
- Allison heavy-duty off-highway automatic transmissions that require a C-4 quality fluid
- Hydraulic systems on industrial and mobile equipment operating over a wide temperature range

⁽¹⁾Obsolete service category.

Note: *Classic ATF is not recommended for use in newer automatic transmissions that require a GM DEXRON[®]-VI, Ford MERCON[®]LV, Ford MERCON[®]SP or Ford MERCON[®]V fluid for warranty coverage, or in continuously variable transmissions (CVTs).*

Features/Benefits

- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent thermal stability and oxidation resistance for long fluid life
- Excellent low-temperature properties
- Protects against wear
- Minimizes sludge and varnish deposits
- Protects against rust and corrosion
- Good seal compatibility
- Suitable for both automotive and industrial applications

**Transmission
Fluid for Older
GM & Ford
Automatic
Transmissions**



Classic ATF®

Typical Properties	
Specific Gravity @ 60°F	0.861
Density, lbs/gal @ 60°F	7.17
Color, ASTM D1500	Red
Flash Point (COC), °C (°F)	212 (414)
Pour Point, °C (°F)	<-40 (<-40)
Viscosity, Brookfield	
cP @ -40°C	14,000
Viscosity, Kinematic	
cSt @ 40°C	32.1
cSt @ 100°C	7.0
Viscosity Index	188
Zinc, wt %	<0.003

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

07-08-16

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

©Phillips 66 Company. Kendall® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.