

Safety Data Sheet

Prepared according to Federal Register / vol. 77, No. 58/ Monday, March 26, 2012 / Rules and Regulations

for

Water Based Coating Materials

Section 1 - Company & Product Identification

Product Name: Water Base Urethane Product Code: WU Flat Colors

Trade Name: All Flat Artist Colors

Manufactured by:

Spectrum Coatings Laboratories, Inc.
217 Chapman Street
Providence, RI 02905
ph:401-781-4847
fax:401-781-1075
web: spectrumcoatings.us
email: paintman97@gmail.com

Emergency Contact Information:

Daytime Information: 8:00am - 4:30pm EST
401-781-4847

24 Hour Emergency Contact:
Chemtrec - 800-424-9300
International: +1 703-527-3887
Emergency Information Only

Product Use: Professional Industrial and Commercial Spray Painting

Not recommended for: Commodity General Public Use

Section 2 - Hazards Identification

GHS Ratings:

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H315	Causes skin irritation
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P264	Wash all exposed areas thoroughly after handling
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see Section 4 and 11 of SDS)
P362	Take off contaminated clothing and wash before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container to suitable waste stream in accordance with local, regional, national, and international regulations.

Signal Word: Danger



Section 3 - Hazardous Ingredient Information

Chemical Name	CAS number	Weight Concentration %
Water	7732-18-5	50.00% - 60.00%
Trade Secret	N/A	10.00% - 20.00%
Polymeric condensate of urea & formaldehyde	9011-05-6	5.00% - 10.00%
Trade Secret	N/A	5.00% - 10.00%
Butyl Cellosolve	111-76-2	1.00% - 5.00%
n-Methyl-2-Pyrrolidone	872-50-4	1.00% - 5.00%
Non-Hazardous Resis Solids	Resin	1.00% - 5.00%

Section 4 - Emergency First Aid Measures

Inhalation: If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Eye Contact: If symptoms develop, move individual away from exposure, and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or if there is any visual difficulty, seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Note to Physician: Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: lung (ie; asthma-like conditions), skin (redness or rash-like symptoms, irritation)

Section 5 - Fire Fighting Measures

Flash Point: 100 C (212 F)

LEL: 1.00

UEL: 11.00

Extinguishing Media: Use water, foam, Carbon Dioxide, or Dry Chemical fire fighting apparatus.

Unusual Fire & Explosion Hazards: This water based solution is non-flammable however, in a fire situation vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, or other ignition sources at locations distant from material handling area. Never use welding or cutting torch on or near containers even when empty, as product and/or product residue can ignite explosively.

Hazardous Products of Combustion: May form oxides of carbon, and nitrogen.

Special Fire Fighting Procedures: Treat all fires as chemical in nature. The use of water may be suitable as an extinguishing media, but will be helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes.

Fire Fighting Equipment: Firemen and emergency responders: wear full turnout gear or Level A equipment, including positive-pressure, self-contained breathing apparatus (SCBA), and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

Section 6 - Accidental Release Measures

Spill and Leak Procedures: Spill supervisor - Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

Small Spills: Ventillate area, and keep sources of ignition and hot metal surfaces isolated from the spill . Absorb liquid using vemiculite, sawdust, speedy-dry, or other suitable floor absorbant material . Use only non-sparking tools to collect and transfer to a suitable container for disposal in accordance with local, and federal regulations.

Large Spills: Eliminate all ignition sources, and ventilate area. Persons not wearing protective wequipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, and prevent material from entering drains, sewers, streams or other bodies of water. Dike spill area with suitable absorbant material or chemical booms to limit spreading. If run-off occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product, and transfer contaminated absorbent, soil and other materials to containers for disposal in accordance with local, state, and federal regulations. Note; use only non-sparking equipment to clean up spills.

Section 7 - Handling and Storage Conditions

Handling Precautions: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers dry and closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Sufficeintly ground container when transferring material from one container to another.

Emergency eyewash fountains and safety showers should be available in the immediate vicinity of potential exposure. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures and pressures, or sudden ingress of air into vacuum equipment, may result in ignitions without the presnce of obvious ignition sources. Any use of this product in elevated temperature, pressurized, or vacuum process should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage Requirements: Store this material in tightly sealed original containers only, in a segregated area with adequate ventilation to prevent a build-up of "fumes" that could pose a safety hazard with regard to personal exposure and fire. Keep all sources of ignition away from storage area, and store material at temperatures between 50 to 80 degrees F.

Section 8 - Exposure Controls & Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Water 7732-18-5	OELs not established	OELs not established	Not Established
Trade Secret N/A	Not Established	Not Established	Not Established
Polymeric condensate of urea & formaldehyde 9011-05-6	OELs not established	OELs not established	PEL 15mg/m3 - TWA (total dust) PEL 5mg/m3 - TWA (respirable dust)
Trade Secret N/A	Not Established	Not Established	Not Established
Butyl Cellosolve 111-76-2	PEL 50ppm - TWA VPEL 25ppm - TWA	TLV 20ppm - TWA	Not Established
n-Methyl-2-Pyrrolidone 872-50-4	OELs not established	OELs not established	PEL 25ppm - TLV
Non-Hazardous Resis Solids Resin	Not Established	Not Established	Not Established

Engineering Controls: Ensure that any processing ovens are vented to prevent the introduction of fumes into the workplace, and to prevent a build up of fume within the oven. Use only explosion proof equipment, and ground

containers and transfer equipment. Use only chemically resistant transfer equipment, and measuring containers.

Recommended Ventilation: General mechanical ventilation may be sufficient to keep product vapor concentrations within specified time-weighted averages. If general ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required.

Eye Protection: The use of safety glasses, chemical goggles, and/or face shields are recommended to safeguard against potential eye contact, irritation, or injury. The availability of eye wash stations when using this product is highly recommended.

Skin Protection: The use of chemical resistant gloves is recommended to prevent repeated or prolonged contact with the skin. Wear impervious clothing and boots. The use of chemical aprons is advised when working with and/or transferring these materials. The availability of safety showers in work areas is recommended.

Respiratory Protection: If workplace exposure limits of product or any component is exceeded, the use of a NIOSH/MSHA respirator will be necessary. In general the use of an organic vapor cartridge with a dust/mist pre-filter will be sufficient. In the absence of proper environmental controls, a NIOSH/MSHA approved air supplied respirator is advised.

Contaminated Equipment: Dispose of the waste in compliance with all Federal, state, regional, and local regulations.

Section 9 - Physical & Chemical Properties

This mixture typically exhibits the following properties under normal circumstances.

<p style="text-align: center;">Appearance Viscous liquid either colored or milky depending on product.</p> <p style="text-align: center;">Physical State Liquid</p> <p style="text-align: center;">Evaporation Rate Slower than ether.</p> <p style="text-align: center;">% Volume Volatile 67.50</p> <p style="text-align: center;">Formula Lb / Gal 9.32</p> <p style="text-align: center;">gms VOC/Liter Less Water 128</p>	<p style="text-align: center;">Odor Strong solvent/ammonia type odor.</p> <p style="text-align: center;">Vapor Density Heavier than air.</p> <p style="text-align: center;">Boiling Range 77 to 173 °C</p> <p style="text-align: center;">Specific Gravity (SG) 1.117</p> <p style="text-align: center;">Lbs VOC/Gallon Less Water 1.06</p>
--	--

Section 10 - Reactivity Data

Components of this mixture may be incompatible with various materials, and will fume certain combustion products. It is recommended that only Spectrum's authorized materials are combined with Spectrum's finished products.

STABLE

The following incompatibilities may exist with components of this product.

Strong oxidizing agents, acids, and alkali/base/caustic solutions, and heat.

Non-reactive material.

Acids, strong oxidizing agents.

Thermal decomposition in the presence of air may yield the following;

May form: aldehydes, carbon dioxide and carbon monoxide, ketones, organic acids.

No hazardous decomposition or by-products are expected.

Oxides of carbon, such as carbon dioxide & carbon monoxide.

Hazardous polymerization will not occur.

Section 11 - Toxicological Information IF NO DATA IS AVAILABLE, THIS SECTION WILL BE BLANK

Mixture Toxicity

Inhalation Toxicity LC50: 5mg/L

Component Toxicity

111-76-2

Butyl Cellosolve

Oral LD50: 1,300 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit) Inhalation LC50: 5 mg/L (Rat)

872-50-4

n-Methyl-2-Pyrrolidone

Oral LD50: 4,150 mg/kg (Rat) Dermal LD50: 5,000 g/kg (Rat) Inhalation LC50: 5 mg/L (Rat)

Primary Routes of Entry:

Inhalation Skin Contact Eye Contact Ingestion

Target Organs:

Blood Kidneys Liver Lungs Reproductive System Skin

Effects of Overexposure

Eye Contact	Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.
Skin Contact	May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use .
Ingestion	Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.
Inhalation	Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symtoms usually occur at air concentrations higher than the recommended exposure limits.
Symptoms of Exposure	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation, stomach or intestinal upset, irritation of the nose,throat & airways, central nervous system depression, high blood sugar, coma .
Target Organ Effects	This material shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Overexposure to this material has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities. No Data
Cancer Information	Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is NOT listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration .
Symtoms of Exposure	Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation, stomach or intestinal upset, irritation of the nose,throat & airways, central nervous system depression, high blood sugar, coma .
Developmental Info.	This material (or a component) may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of this product during pregnancy can cause birth defects in humans.
Developmental	This material (or a component) may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of this product during pregnancy can cause birth defects in humans.

Carcinogenicity: The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing) .

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			N/A

Section 12 - Ecological Information

IF NO DATA IS AVAILABLE, THIS SECTION WILL BE BLANK

Component Ecotoxicity

Section 13 - Waste Disposal Considerations

As the US EPA, state, regional, and other regulatory agencies may have jurisdiction over the disposal of your facility's hazardous waste, it is incumbent upon you, the hazardous waste generator, to learn of and satisfy all the requirements which affect you. Dispose of the hazardous waste at a properly licensed and permitted disposal site or facility. Ensure conformity to all applicable hazardous waste disposal regulations.

The US EPA Hazardous Waste Numbers which follow are applicable to this unadulterated product if the product enters the "waste stream." Refer to Title 40 of the Code of Federal Regulations, Part 261 (40 CFR 261). This part of the Code identifies solid wastes which are subject to regulation under various sections of the Code and which are subject to the notification requirements of Section 3010 of the Resource Conservation and Recovery Act (RCRA).

Section 14 - Transportation Information

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Non-Hazardous Water Base Paint	N/A	N/A	N/A

Section 15 - Regulatory Information

Other regulatory information is listed where applicable.

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

872-50-4 n-Methyl-2-Pyrrolidone 1 to 5 %
Trade Secret 10 to 20 %

Commonwealth of Massachusetts "Right to Know": This product contains the following toxic or hazardous substances which appear on the Massachusetts Substance List:

n-Methyl-2-Pyrrolidone 1 to 5 %
Butyl Cellosolve 1 to 5 %

New Jersey Worker and Community Right To Know Hazardous Substance List: The following substances appear on the New Jersey Right To Know Hazardous Substance List.

n-Methyl-2-Pyrrolidone 1 to 5 %
Butyl Cellosolve 1 to 5 %

Commonwealth of Pennsylvania Worker and Community Right-To-Know Act: This product contains the following chemicals which appear on the Pennsylvania Hazardous Substance List:

872-50-4
111-76-2

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

EU Risk Phrases

Safety Phrase

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory:

- None

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations, part 372.

872-50-4 n-Methyl-2-Pyrrolidone 1.0 - 5%

Section 16 - Other Information

Hazardous Material Information System (HMIS)

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	J

HMIS & NFPA Hazard Rating

Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



NON-WARRANTY. The information presented in this publication is based upon the research and experience Spectrum Coatings and its suppliers. No representation or warranty is made concerning the accuracy or completeness of the information presented in this publication. Spectrum Coatings makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Spectrum Coatings are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Spectrum Coatings shall in no event be liable for any special, incidental, or consequential damages.

Reviewer Revision

Date Prepared: 6/22/2015