

# Hot Pressure Washer PW-H80 D1921P T

**Order Code: IDAC40360**

The PW-H80 series, combining high water flow and high pressure levels for routine cleaning all sectors. The exclusive IPC Pump and the high efficiency IPC Motor offers great comfortable use and assures durability and reliability.

The stainless steel IPC boiler reduces the difficult and timeconsuming task of cleaning the coil to the level of routine maintenance.



## Uninterrupted work

Uninterrupted work with:

- IPC exclusive pump
- IPC exclusive s.steel boiler
- 25 litres fuel tank capacity



## Low maintenance costs

Minimized operative and maintenance costs  
T-Stabilizer

- By ensuring a more constant temperature, PW-H 80 maximizes its efficiency vs heating performance
- Easy access to all internal components



## Full controls, ergonomics and safe

- Full control over your fuction
- Ergonomic in use Safety devices
- Intelligent total stop
- Micro leakage control
- Dry running control
- Signal pilot for fuel, detergent and anti-scale lack

**Versatile with great performances**



# IPC

<b>Technical Specifications</b>		<b>PW-H80 D1921P T 400/50</b>
Operating pressure	bar	40÷190
Volume	l/h	650÷1300
Outlet water temp.	°C	30÷140
Pressure and steam phase regulation		Yes

<b>Electrical Features</b>		<b>PW-H80 D1921P T 400/50</b>
Power supply	Ph/V/hz	3 ~ 400V - 50Hz
Absorbed power	Kw	8,5
Motor pole		4 -1400
Remote control		New intelligent total-stop
Dry running control		Yes
Leakage control		Yes
Signal pilot for fuel, detergent and anti-scale lack		Fuel/anti-scale lack

<b>Hydraulic Features</b>		<b>PW-H80 D1921P T 400/50</b>
Pump		Ipc plunger
Pump head		Brass
Pistons		Full ceramic
Detergent tank		25
Detergent delivery		High pressure
Antiscale device		Yes
Descaling tank		2 lt

<b>Thermal Features</b>		<b>PW-H80 D1921P T 400/50</b>
Boiler type		Stainless steel
Coil		Pm40 40mt
Burner power	Kw	85,5
Fuel consumption (full temp / ecoselect mode)	Kg/H	7,4/ 5,9
Fan motor		Separated
Fuel tank		25l

<b>Dimensions &amp; Weight</b>		<b>PW-H80 D1921P T 400/50</b>
Weight	Kg	171,6
Dimensions	LxWxH	109X70X87
Frame-structure		Plastic material - painted steel
Versions		4 Wheels

<b>Packaging Characteristics</b>		<b>PW-H80 D1921P T 400/50</b>
Type		Palletized carton
Dimensions (LxWxH)	cm	131x78x104
Volume	m3	1,06
Weight	Kg	189,8
Complete pallet quantity		-

<b>Standard Equipment</b>		<b>PW-H80 D192P T 400/50</b>
IPPR40016	Handgrip	G500 + PROL 330 + M22 SW
TBAP40009	High pressure hose	R2 10MT 5/16
LCPR12983	Lance	EXTENSION PD70
UGLN49995	Ugello alta pressione	2x H.P. 25°

<b>Optional Accessories</b>		<b>PW-H80 D1921P T 400/50</b>
Optional		Turbo nozzle
KTRI88654		Hose reel
SPID24911		Rotating hydro brush
SPID24939		Fixed hydro-brush lance
LCPR24937		Foam head
KTRI29377		Feeding kit
LCLC41140		Lance for washing floors
TBAP23853/24406		Drain kit
KTRI29366		Plunger ejectore device
RCIN10810		Hose coupling

Ip Cleaning S.p.A.  
Viale Treviso 63  
30026 Summaga di Portogruaro  
(VE) / ITALY

Tel. ++39 0421 205511  
Fax ++39 0421 204227

info@ipcleaning.com  
www.ipcleaning.com

