

C7 LED

DISCONTINUED
Limited Stock Available



APPLICATION

Suitable for corridor, living room and bedroom.

FEATURES:

- UV-resistant opal white acrylic diffuser and with twin steel ring surround design. Die-formed cold-roll steel back plate and lens holding band trim.
- Brushed nickel finish.

LED:


- 3000K color temperature standard.
- 70 lm/W LED.
- CRI: >80
- 50,000 hours.

ELECTRICAL:

- Fixture for ambient minimum operating temperatures from -5°F (-20°C) ~ 105°F (40°C).
- Power Factor: >0.95
- Input Voltage: 120Vac, 60Hz.

LISTING:

- ETL listed. (US, CANADA)
- Suitable for damp locations.
- 5 years limited warranty.
- Energy star listed.



Specifications: C7-12-15LED

Diameter: 12 (304)
Height: 3 (76)

Specifications: C7-16-23LED

Diameter: 16 (406)
Height: 3-1/2 (87)

All dimensions are in inches (millimeters).

CONFIGURATIONS

	LED Watts	Lumen Output	Lumen Efficiency
C7-12-15ALE	15W	1050 lm	70 lm/W
C7-16-23LED	25W	1750 lm	

ORDERING INFORMATION

EXAMPLE: C7-12-15ALE-30K-120-DM

MODEL		LED		COLOR TEMP.		VOLTAGE		DIMMING		OPTION	
C7-12	12" Dia.	15ALE	15 Watts Power	-30K	3000K (Std.)	120	120V (Std.)	DM	Triac Dimming (Std.)	REM7	7W Remote EM ¹ (32°F (0°C) ~ 131°F (55°C))
C7-16	16" Dia.	23LED	25 Watts Power								

NOTE:

1. Remote mount only available with 23LED.

LED 2-RING OVAL CEILING

CO2



APPLICATION

This decorative LED oval-shaped ceiling light is ideal for kitchens, workshops, offices and many other light commercial or residential settings..

FEATURES:

- Satin nickel finish, opal white diffuser, and oval shape.
- Contemporary style flushmount oval ceiling.
- Suitable for surface mounting.
- Frosted PC Diffuser.

LED:


- 3000K color temperature standard.
- LED wattage: 53W
- CRI: >90
- Nominal Lamp Life: 100,000 hours
- Reported L70 hours: +73,000 (51.2°C)
- Rated R9 Value: 10

ELECTRICAL:

- Fixture for ambient minimum operating temperatures from -4°F (-20°C) ~ 113°F (45°C).
- Power Factor: >0.90
- Dimming Control: 1-10V (10%~100%)
- Input Voltage: 120V- 277V, 60HZ.

LISTING:

- ETL listed. (US, CANADA)
- 5 years limited warranty.
- JA8 Compliant.
- Title 24.



Specifications: CO2

Diameter: 18-9/32 (464)
Height: 4-7/32" (107)
Length: 32-3/8 (822)
Weight: 10.8 lbs (4.9 kg)

All dimensions are in inches (millimeters).

CONFIGURATIONS

	LED Watts	Lumen Output	Lumen Efficiency
CO2	53W	4322 lm	83 lm/W

ORDERING INFORMATION

EXAMPLE: CO2-53LED-30K-UNV-DM

MODEL		LED		COLOR TEMP.		VOLTAGE		DIMMING	
CO2	32"	53LED	53 Watts Power	-30K	3000K (Std.)	UNV	120-277V (Std.)	DM	1-10V Dimming (10%-100%)