

CADXR



FEATURES:

- City of Chicago Approved (120 minute emergency operation), heavy duty emergency lighting that is efficient and easy to install. It is completely self-contained and fully automatic.
- Durable 20-gauge steel construction with powder coated finish.
- 90+ minute emergency operation.
- Test switch and charge rate indicator.
- Remote capable on all model.
- Neutral white or black finish.

MOUNTING:

- Universal knockout pattern on back for wall mount.
- Side and top knockouts for conduit feed applications.

ELECTRICAL:

- 120/277V, 60Hz dual voltage operation standard.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (Low voltage disconnect) prevents battery from deep discharge.

LAMPS:


- Two 6V 12W.
- Fully Adjustable, two glare-free halogen par36 lamp heads.

BATTERY:

- Maintenance-free, 6V sealed lead acid rechargeable battery.
- Remote capacity of up to 26W and 76W available on 50W and 100W models respectively.
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Internal solid-state transfer switch automatically connects the internal battery to LEDs for minimum 120 minute emergency illumination.

LISTING:

- 5 years limited warranty on all electronics and housing. Battery prorated for 2 years.
- UL listed for damp locations & meets UL924, National Electrical Code, ANSI/NFPA 70 and the Life Safety Code ANSI/NFPA 101.



Specifications: 27W

Width 1: 12-1/4 (311)
 Height 1: 5 (127)
 Height 2: 11-13/16 (300)
 Depth: 2-1/2 (63)

Specifications: 50W

Width 1: 14-9/16 (369)
 Width 2: 16-11/16 (423)
 Height 1: 10-1/2 (266)
 Height 2: 14-3/4 (374)
 Depth: 4-1/4 (107)

Specifications: 100W

Width 1: 14-1/2 (368)
 Width 2: 16-5/8 (422)
 Height 1: 7-15/16 (201)
 Height 2: 17-5/16 (439)
 Depth: 2-1/2 (63)

All dimensions are in inches (millimeters).

ELECTRICAL INFORMATION

	Input Watts (W)	Input Amps (A)
CADXR-6-27	120V: 11.0 W	120V: 0.11 A
	277V: 11.0 W	277V: 0.04 A
CADXR-6-50	120V: 18.0 W	120V: 0.17 A
	277V: 18.0 W	277V: 0.07 A
CADXR-12-50	120V: 26.0 W	120V: 0.25 A
	277V: 26.0 W	277V: 0.10 A
CADXR-6-100	120V: 23.0 W	120V: 0.21 A
	277V: 23.0 W	277V: 0.10 A
CADXR-12-100	120V: 32.0 W	120V: 0.30 A
	277V: 32.0 W	277V: 0.13 A

ORDERING INFORMATION:

EXAMPLE: CADXR-6-27-WH

MODEL	VOLTAGE	WATTS	HOUSING COLOR
CADXR	(Blank) 6V ¹	27 27W	WH White Housing
	6 6V ²	50 50W	BK Black Housing
	12 12V ²	100 100W	

NOTES:

1. Available in 27 watt only.
2. Available only in 50 watt & 100 watt models.