

ODW

Project Name:	
Type:	



APPLICATION

This indoor & exterior decorative wall sconce is ideal for both commercial and residential application. Ideal for building entrances or walkways with wall mounting.

FEATURES:

- Solid metal accent bars.
- Sealed and gasketed construction.
- Oven cured no VOC acrylic powder coat.
- Fabricated 1/8" thick white acrylic diffuser, F1 rated, UV stable, UL-94 HB flame class rated.
- Easy relamping.

MOUNTING:

- Mounts to standard electrical junction box (by others) with provided hardware.

LAMP:


- Fluorescent or low energy.
- Lamps furnished by others.

ELECTRICAL:

- High power factor electronic ballast, 0° F / -18° C starting temperature (fluorescent).

LISTING:

- 5 year product warranty.
- UL listed for wet location mounting 4' above grade.
- ARRA compliant.



Specifications: ODW

Height: 16 (406)
 Width: 7-1/4 (184)
 Depth: 5-1/2 (140)

All dimensions are in inches (millimeters).

ORDERING INFORMATION

EXAMPLE: ODW-226-UNV-NA

MODEL	LAMP TYPE	VOLTAGE	FINISH	OPTIONS
ODW	126	(1) CF26 DTT, 4-Pin	NA Natural Aluminum (Std.) GR Gray LBZ Light Bronze WH White BK Black	LP Lamps Provided (Specify Color Temperature) EM Emergency battery (32°F ~ 122°F / 0°C ~ 50°C) EMC CEC compliant EM ¹ BG Bird Guard, Stainless Steel Spikes
	1CF27	(1) CF27, 4-Pin, 2G11 Base		
	213	(2) CF13 DTT, 4-Pin		
	218	(2) CF18 DTT, 4-Pin		
	226	(2) CF26 TRT, 4-Pin		
		UNV 120-277V 120 120V 277 277V	* Available custom color (RAL) Please provide us with the RAL number.	

NOTES:

1. Check with factory for more details.