



FLOORING, INC.

115 Old Belwood Road
Calhoun, Georgia 30701-3606
E-Mail: sales@daltonian.com

706-602-7478
1-800-788-1408
FAX 706-602-7823

SOUND BARRIER SUPREME

- A super Hi-Density underlayment made especially for use with all laminate and other hard-surface "floating" floors.
- New moisture 3 mil barrier film.
- Excellent sound absorption- Rating of 71db
- Eliminates hollow clacking sounds
- Smoothes out minor sub-floor irregularities
- Made with 100% Allergenic Resistant "Ultra Fresh ®" materials, which resist odor causing mold and mildew
- Recommended for use with Radiant Heat Floors.

INSTALLATION INSTRUCTIONS

- (1) Start in a corner. Unroll Sound Barrier Supreme underlayment over subfloor with vapor barrier film **down** against subfloor. (Film Side Down) -Be sure tape strip side is next to the wall and overlapping lip is toward open room.
- (2) Roll out next row in the same manner butting foam close to first row and covering overlapping moisture barrier lip. Do not overlap foam pad just the moisture barrier lip.
- (3) Remove tape liner and secure the overlapping moisture barrier to it. Continue with installation. Seal all open seams with aggressive adhesive plastic tape.
- (4) Install flooring per manufacturers instructions.

20-YEAR LIMITED WARRANTY

DALTONIAN FLOORING INC., (DFI) warrants that Sound Barrier Supreme (SBS) will conform to the published product specifications, subject to manufacturing tolerances, will be merchantable for the ordinary purposes for which such goods are used and will be free of defects in material and workmanship at the time of shipment. DFI further warrants that it will replace DFI's defective products and will reimburse purchaser the original purchase price of any excessive abrasion resulting solely from a defect in DFI's Sound Barrier Supreme that caused a substandard performance to any valid warranty of the laminate manufacturer.

This commercial warranty gives the purchaser specific legal rights and the purchaser may also have other rights, which vary from state to state.

This commercial warranty will be effective only if Sound Barrier Supreme underlayment is installed and maintained in full compliance with the laminate floor manufacturer's instruction, recommendations and specifications.

DFI does not assume any liability for faulty installation or lack of maintenance or improper maintenance.

MATERIAL CONTENT: SYNTHETIC RUBBER FOAM

THICKNESS (INCHES):	.085	
DENSITY (CUBIC FT):	20-Lb. min.	ASTM D3676
PILL TEST :	PASS	

IMPACT SOUND TRANSMISSION:	70db
width:	6'
Length:	75'
	(50 yd ² per roll)