



FLOORING, INC.

130 Executive Drive  
Calhoun, Georgia 30701-3067  
E-Mail: sales@daltonian.com

706-602-7478  
WATS 1-800-788-1408  
FAX 706-602-7823

## SYNTHETIC FIBER CUSHION

- Designed for all commercial and residential installations.
- Light, medium and high traffic areas
- Non allergenic, will not support bacterial growth
- Sound absorbent, excellent thermal insulator
- Environmentally friendly, prolongs life of carpet
- Thermo-bonded surface for easy installation
- Made from carpet fibers (polypropylene and nylon), free from any plastic, lumps, or hard spots
- No smells, no odors, extremely low VOC's. All products pass the CRI Green Label Plus test for excellent indoor air quality.
- All rolls shipped on a core for easy handling

	FIBER 24	FIBER 28	FIBER 32	FIBER 40	FIBER 32DS (double-stick)
WEIGHT (ozs)					
THICKNESS	.275	.300	.360	.420	.310
DENSITY (lbs./cu.ft)	7.0	8.0	8.2	9.0	9.0
TENSILE STRENGTH (lbs)					
LENGTH	161	285	313	340	245
WIDTH	215	293	340	354	290
PILL TEST	PASS	PASS	PASS	PASS	PASS
FHA TYPE/CLASS	H1&2	H1&2	H1&2	H1&2	H1&2
RADIANT PANEL ASTME 648	CLASS 1	CLASS 1	CLASS 1	CLASS 1	CLASS 1
ROLL WIDTH	6'/12'	6'/12'	6'/12'	6'/12'	6'/12'
ROLL LENGTH	60'/60'	60'/60'	60'/60'	60'/60'	60'/60'

Qualifies for potential LEED points as a product made from 100% recycled material and can itself be recycled:

1 Point for 10% post industrial recycled content	MR 4.1
1 Point for low emitting VOC's	EQ 4.3
1 Point for 20% post industrial recycled content	MR 4.2
<b>TOTAL</b>	<b>3 Points</b>