

DALTONIAN

FLOORING, INC.

115 Old Belwood Road
Calhoun, Georgia 30701-3606
E-Mail: sales@daltonian.com

VERNON *House*
HOSPITALITY CARPET

706-602-7478
1-800-788-1408
FAX 706-602-7823

CONGO

Manufacturing Process	Woven Incorporated Wilton
Construction	Face to Face Wilton
Pile Fiber Content	100% BCF Olefin
Pile Weight	52-oz. y ²
Total Height375
Dye Method	100% Solution Dyed
Pattern Repeat	19.75"W X 19.75L"
FLAMMABILITY	
DOC FF-1-70-ASTM D2859	PASS
ASTM E 648-97	CLASS II
Application: Commercial & Residential	
Roll Size: 13'2"x 82'	
Available Colors: 819 Black	
Warranty: 1 year mfg defects and 5 years pro-rated wear warranty	

PRODUCT DISCLAIMER

- Our Woven Wilton carpets have no ultraviolet protection. Any sunlight- even through treated windows may cause a color change & fiber degradation.
- Shading, also referred to as watermarking, roll crush or reverse pile, can occur on all cut pile materials, which is an inherent effect on the product regardless of fiber or quality. The cause is unknown, & the rate of incidence is unpredictable despite extensive industry research. Further, there is no method to make it occur or likewise a method of prevention, & therefore is not considered to be a manufacturing defect. As a result, claims will not be considered for this condition.
- Shedding is a natural characteristic of all carpets. Loose bits of fiber may appear on the carpet surface & can be removed with gentle vacuuming. Improper maintenance, dragging objects or overly aggressive vacuum methods can distort pile & cause excessive fuzzing or burns.
- As with any textile, actual pattern repeats may vary slightly from the published pattern repeat. These are woven products through a jute backing. Daltonian Flooring does not guarantee a perfect pattern match at seams.
- Recommended for conventional tack & pad installation over a firm dense pad or double-glued over a firm dense pad.
- Direct glue-down installations will have a 1-yr mfg. Defects warranty, but no wear warranty.
- For optimum side match & finished seam appearance, this product should be installed with seams running perpendicular to major (outside) lighting sources.
- No claim will be considered on carpet that is cut or installed with visible defects or installed with pattern mismatch.
- We do not warranty broadloom on stair installations, & as such we will not entertain any claims on such installations.
- Chair mats are recommended under office chairs with roller casters to preserve appearance & act as a deterrent towards accelerated wear.
- Due to variations in dye lot, actual carpet colors may vary.
- Specifications may vary within normal industry tolerance.
- Rebond or low-density urethane cushions are not recommended for use with this carpet.

Available in custom rug sizes