

# DALTONIAN

FLOORING, INC.

115 Old Belwood Road  
Calhoun, Georgia 30701-3606  
E-Mail: sales@daltonian.com

706-602-7478  
1-800-788-1408  
FAX 706-602-7823

VERNON *House*  
HOSPITALITY CARPET

## TRADE WINDS

Manufacturing Process .....	Flat Woven Wilton
Pile Fiber Content .....	100% Berclon Olefin
Total Weight .....	40-oz. y <sup>2</sup>
Total Height .....	0.196"
Dye Method.....	100% Solution Dyed
FLAMMABILITY	
DOC FF-1-70-ASTM D2859 .....	PASS
Application.....	Commercial & Residential

### PRODUCT DISCLAIMER

- Our Soft Weave carpets have ultraviolet protection and can be used outdoors and indoors.
- As with any textile, actual pattern repeats may vary slightly from the published pattern repeat. These are woven products through a synthetic backing, additionally; product widths may vary slightly from the published widths. Daltonian Flooring does not guarantee a perfect pattern match at the seams.
- For optimum side match and finished seem appearance, this product should be installed with seams running perpendicular to major (outside) lighting sources.
- No claim will be considered on carpet that is cut or installed with visible defects or installed with pattern mismatch.
- We do not warranty broadloom on stair installations, and as such we will not entertain any claims on such installations.
- Chair mats are recommended under office chairs with roller casters to preserve appearance and act as a deterrent towards accelerated wear.
- Due to variations in dye lot, actual carpet colors may vary.
- Specifications may vary within normal industry tolerance.
- Rebond or low-density urethane cushions are not recommended for use with this carpet.

### PRODUCT INFORMATION

- All Soft Weave carpets are very easy to clean (even bleach cleanable). They are a unique combination of a natural sisal look and practically.
- Soft Weave carpets can be installed by traditional wall to wall method using short pin tack strips and Daltonian cushion. Can also be done using the double stick method over low pile, dense padding or fully adhered directly to subfloor.
- Caution- do not loose lay this carpet as it will move and slide on the floor.
- Can be installed indoors or outdoors. "Weathersafe" construction.
- Seams should be made only by a professional installer experienced in working with "natural" type products like sisal or seagrass. Cutting should be done from the face using a sharp cutter held at a slight angle and following the line between the ribs.
- All cut edges should be treated with a cold sealer adhesive.
- Offered in 13'2" broadloom and custom rugs.

**Available in custom rug sizes**