

WHITE KRAFT PAPER

CHARACTERISTICS (COATED)

- 84 - 87% ISO Brightness
- One side light-coated
- Excellent printing capabilities

CHARACTERISTICS (UNCOATED)

- 87 - 88% ISO Brightness
- Three types: Regular, High White, OBA-Free
- Premier runability & convertibility
- Excellent strength & printing performance
- OBA-Free is designed to stand food contact

OVERVIEW

Printing Method	Flexograph Offset Rotogravure
-----------------	-------------------------------------

APPLICATIONS



Shopping Bags



Flour Packaging



Ice Cream
Cone Wrappers



Tea Bag Tags



Envelopes

White Kraft Coated

Property	Unit	Test Method Reference	Basis Weight					
Basis Weight	g/m ²	ISO 536	80±3	90±3	100±3	120±3	135±3	145±3
Thickness	µm	ISO 534	86±4	97±4	105±4	128±4	144±4	154±4
Brightness	%	ISO 2470/1	86±1.5	86±1.5	86±1.5	86±1.5	86±1.5	86±1.5
Roughness	µm	ISO 8791/4	≤2.8	≤2.8	≤2.7	≤2.7	≤3.2	≤3.2
Bursting Strength	kPa	ISO 2758	≥230	≥260	≥300	≥330	≥330	≥330

White Kraft Uncoated

Property	Unit	Test Method Reference	Basis Weight			
Basis Weight	g/m ²	ISO 536	80±4	100±4	110±4	120±4
Thickness	µm	ISO 534	98±4	121±4	135±4	146±4
Brightness	%	ISO 2470/1	87±2	87±2	87±2	87±2
Roughness	µm	ISO 8791/4	5±0.5	5±0.5	5±0.5	5±0.5
Bursting Strength	kPa	ISO 2758	≥260	≥280	≥330	≥360

