

ZENITH



Zenith gives you a higher yield advantage and offers premium stiffness when compared to the standard printing and packaging board. Aesthetically pleasing with a 91 brightness coating and a double coating top side and a single coating back side. Zenith has excellent performance for printing, folding, die cutting, scoring and a wide range of promotional, premium packaging, card and cover applications.

FEATURES & BENEFITS

- Higher yield advantage than standard printing and packaging board.
- Aesthetically pleasing with a 91 brightness coating and a double coating top side and single coating back side.
- Optimum performance on high-speed conversion process.
- Excellent performance in printing, folding, die cutting and scoring.

END USE APPLICATIONS



OVERVIEW

Surface	CIS
Weight (g/m ²)	12pt / 215 gsm 14pt / 235 gsm 15pt / 250 gsm 16.1pt / 270 gsm 18.1pt / 295 gsm 20.1pt / 325 gsm 22pt / 350 gsm 24pt / 380 gsm
Format	Sheets / Rolls
Printing Methods	Offset Rotogravure Letterpress Flexography
Certificates	ISO 14001 ISO 9001 OHSAS 18001 PEFC FDA Compliant

Property	Unit	Test Method Reference	Basis Weight							
			215	235	250	270	295	325	350	380
Basis Weight	g/m ² (±3)	ISO 536	215	235	250	270	295	325	350	380
Caliper	pt (±0.4)		12	14	15	16.1	18.1	20.1	22	24
Thickness	µm (±10)	ISO 534	305	355	380	410	460	510	560	610
Brightness	%ISO	7452 OM-92	91.5	91.5	91.5	91.5	91.5	91.5	91.5	91.5
Moisture	%	ISO 2471	6.5±1.0	6.5±1.0	6.5±1.0	6.5±1.0	6.5±1.0	6.5±1.0	6.5±1.0	6.5±1.0
PPS (Top)	µm	ISO 8791-4	1.4±0.3	1.4±0.3	1.4±0.3	1.4±0.3	1.4±0.3	1.4±0.3	1.4±0.3	1.4±0.3
75° Gloss (Top)	%	T 480	≤45	≤45	≤45	≤45	≤45	≤45	≤45	≤45

