



POINT HELIPORT FLOODLIGHT PHF GROUND MOUNT FLOODLIGHT

Compliances: UL Listed to UL 1598 Wet Locations
CSA Listed to C22.2 No. 250.0-04 Canada

The PHF-53004 is a high intensity 120 or 220-240 volts ground level mounted helipad floodlight intended to "wash" the pad with light or to provide additional ground area floodlighting. The PHF-53004 floodlight is mounted to 2-3/8 inch (60 mm) pipe slipfitter. With option "-2P", the PHF assembly mounts to the die-cast aluminum FAA certified breakable coupling. The overall height is adjustable based on the length of 2-inch EMT pipe ordered. The floodlight may be ordered with a 500, 1000 or 1500 watt halogen lamp. The floodlight is a listed product of Hubbell Lighting.

Point Type	Lamp & Voltage	Mounting Options
PHF-53004	1000Q: 1000 watts, 120v 1000Q2: 1000 watts, 230v 1500Q2: 1500 watts, 230v 500Q2: 500 watts, 230v	SF: Slipfitter 2-3/8 (60mm) 2P: 2-inch EMT Coupling PLB: Light Base & Baseplate -2S PLS: Shallow Base & Baseplate -2S

Note: Specify overall height

For mounting options & plan details, see file 0MOUNTINGS

PHF-53004-1500Q-SF-2P
SHOWN WITH PL40301-2S BASEPLATE

Instruction Sheet: IS53004
Lamp Life (hours): 2000
Weight: 10 lbs 4.5 kg
Volume: 1.5 ft³ .042 m³



REPLACEMENT PARTS

PL10041 Breakable Coupling
PL10341-500-1 Lamp 500w Halogen
PL10341-500-2 Lamp 500w Halogen
PL10341-1000-1 Lamp 1000w Halogen
PL10341-1000-2 Lamp 1000w Halogen
PL10341-1500-1 Lamp 1500w Halogen
PL10341-1500-2 Lamp 1500w Halogen
PL40301-2S Baseplate 2-inch NPS
PL10049-4-6 Gasket, Baseplate

