

# L5

## Suspended Linear LED Luminaire

For Ambient Lighting



Project: \_\_\_\_\_  
 Cat#: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Notes: \_\_\_\_\_

### Product Description

The L5 Suspended direct/indirect linear LED Luminaire is small profile and suitable for individual or continuous row mounting. The L5's LED technology offers significant energy efficiency over traditional sources to achieve top of the industry watts per square foot performance.

### Construction

The L5 is constructed out of die formed steel and aluminum and is available in standard white or custom powder coat finishes. Lenses are high light transmission UV stable acrylic. Mounting to grid or drywall ceiling via fully adjustable aircraft cables.

### Light Source

Light source comprised of mid power LEDs that are thermally engineered to ensure optimal efficacy's up to 96 lumens per watt and 80+ CRI. Luminaire light output guaranteed to achieve a minimum of 70% luminaire output over 100,000 hours at typical 25 deg. C operating conditions. LED components and luminaires are compliant with IESNA LM80.

### Certification and Warranty

Luminaires carry a limited 5 year warranty and all luminaires are UL listed for indoor damp rated lighting applications.


### Fixture Options

Example L550-82-3000-35K-M-A4-G1-WH-16

Series	L550		L550
Distribution	82	80%up / 20%dn Consult Factor for custom distributions	82
Light Level	3000 4000 5000	3000lm per 4' section 4000lm per 4' section 5000lm per 4' section	
Color	30K 35K 40K	3000K 3500K 4000K	
Driver	STD 010 DAL	STD Switched Driver 0-10 volt Dimming to 5% DALI Driver	
Power	M 3	120-277 347	
Mounting	A4	Aircraft Cable 4' Adjustable	A4
Ceiling	G1 G9 GS ST	15/16" Grid Ceiling 9/16" Grid Ceiling Slot Grid Ceiling Drywall/Structure	
Finish	WH CC	White Powder coat Finish Custom Color Finish	
Length	04 08 xx	Individual Individual Row Length (4' Increments)	
Options			

### Performance

4' Output Package	Lumens	Watts	Lumens/Watt
4000 nominal	4226	44	96
3000 nominal	3146	34	93
5000 nominal	5362	63	85



80/20 – Standard  
 4246 lumens  
 84% up - 16%  
 down  
 96 lm/W

### Dimensions

