

## OUTRIGGER SPREADS AND LOADS

ALL DIMENSIONS AND WEIGHTS ARE APPROXIMATE

Boom Type	FRONT Outrigger Spread in Ft. In.	REAR Outrigger Spread in Ft. In.	FRONT to REAR Outrigger Spread in Ft. In.	MAX. FRONT Outrigger Load LBS.	MAX. REAR Outrigger Load LBS.	MAX. Outrigger Soil* PSI FRONT / REAR
<b>Schwing America Inc.</b>						
20M Z	12' 8'	7' 1"	15' 4"	24,730	15,740	315-200 / 44-28
S 31 XT**	20' 5"	18' 8"	24' 5"	39,700	30,900	203-69 / 158-54
S 45/47 SX	27' 3"	27' 3"	29' 0"	58,500	56,200	362-102 / 348-98
KVM 52/55	31' 2"	31' 2"	34' 2"	60,000	60,000	220-104 / 220-104
S 58/61 SX	29' 2"	41' 1"	37' 9"	78,680	83,176	157-51 / 166-54
<b>Putzmeister America, Inc.</b>						
38Z-5	20' 8"	23' 11"	22' 11"	43,388	46,985	
TB 110	23' 1"	26' 9"	27' 5"	30,350	34,395	

\*With Factory Supplied Dunnage

Updated: July 2016