

SPECIFICATIONS

Pump Kit on S 20

2023-3 110/75 MPS

	U.S.	Metric
Theor. Concrete Output Per Hour (cubic yards - cubic meters)	130	99
Maximum Pressure on Concrete (psi - bar)	1161	80
Maximum Strokes Per Minute	20	20
Material Cylinder Diameter (in. - mm)	9	230
Material Cylinder Stroke Length (in. - mm)	79	2000
Differential Cylinder Size (in. - mm)	4.3	110
Maximum Aggregate Size (in. - mm)	2.5	63.5

Boom Specifications

S 20

	U.S.	Metric
Pipeline Diameter (in. - mm)	5	125
Vertical Reach (ft.-in. - m)	63-9	19.4
Horizontal Reach (ft.-in. - m)	51-10	15.8
Net Horizontal Reach (ft.-in.- m)	44-4	13.5
Unfolding Height (ft.-in. - m)	12-8	3.9
Section Lengths		
First Section (ft.-in. - m)	16-11	5.1
Second Section (ft.-in. - m)	11-7	3.5
Third Section (ft.-in. - m)	11-8	3.6
Fourth Section (ft.-in. - m)	11-8	3.6
Slewing Range (degrees)	730°	730°
End hose length (ft. - m)	10	3

Specifications are subject to change without prior notice.

