

Job Name: _____

Submitted by: _____ Date: _____

Spec Section: _____

Job Location: _____

Engineer/Architect: _____

Approval: _____ Date: _____

Size	Item Number
1/2"	106 1015-__C
3/4"	106 1020-__C
1"	106 1025-__C
1 1/4"	106 1032-__C
1 1/2"	106 1040-__C
2"	106 1050-__C

Specification

Oventrop flex hoses are made of EPDM with a 304 single stainless steel braid.

Working temperature range: 5 to 230 °F

Standard connection: Brass Fixed MNPT x Brass Swivel MNPT

Example hose selection:

3/4" Hose with 24" overall length
Item number - 106 1020-24C

Size	Lengths [in.]	Hose Type	Minimum Bend Radius	Maximum Working Pressure
1/2"	12, 18, 24, 36	304 stainless steel braided EPDM	5"	375 PSI
3/4"	12, 18, 24, 36		7"	300 PSI
1"	12, 18, 24, 36		7"	225 PSI
1 1/4"	18, 24, 36		12"	200 PSI
1 1/2"	18, 24, 36		12"	175 PSI
2"	24, 36		20"	150 PSI



Gasket Less Swivel Connection 1/2" - 1"
BA-U Fiber Gasket 1-1/4" - 2"