



Stitch Cats

by nancy nicholson




FREE PATTERN



Cattin' Around - Finished Size 26½" x 47½"

Featuring fabrics from the
Stitch Cats collection by Nancy Nicholson
Design by Sheri Green for Clothworks

www.clothworks.com info@clothworks.com



Materials

Yardages based on 42" wide fabric

⅓ yd	White Stitch Cats Panel (Y2579-1)*
⅓ yd	9 patch blocks: Khaki Solid (AMB-12)
⅓ yd	9 patch blocks: Dk Orange Solid (AMB-37)
⅓ yd	9 patch blocks: Lt Wine Solid (AMB-47)
⅓ yd	9 patch blocks: Dk Gold Solid (AMB-69)
⅓ yd	9 patch blocks: Lt Tomato Solid (AMB-79)
⅓ yd	9 patch blocks: Turquoise Solid (AMB-101)
¼ yd	Appliqué: Black Solid (AMB-3)
⅓ yd	Inner Border & 9 patch blocks: Dk Brick Solid (AMB-52)
¾ yd	Outer Border & 9 patch blocks: Lt Teal Birds (Y2581-103)
⅓ yd	Binding & 9 patch blocks: Wine Dots (Y2583-48)
2 ⅓ yds	Backing: White Cats (Y2580-1)

Also used: Embroidery floss for cat faces,
½ yd Steam a Seam II™ for paw print appliqué

*Only 4 square blocks of the Stitch Cats Panel will be used; the remaining 2 rectangular blocks may be reserved for another project

Cut the Fabrics

WOF = Width of Fabric LOF = Length of Fabric

Note: We recommend starching all fabrics before cutting

From the Stitch Cats Panel: Fussycut (4) 10½" squares centered on the cat motifs with equivalent space in the foreground.

From each of the fabrics for the 9 patch blocks: Cut (4) 4" blocks

From the Dk Brick Solid for the Inner Border: Cut 1" strips x WOF. Seam together where needed.

From the Lt Teal Birds for the Outer Border: Cut 3" strips x WOF. Seam together where needed.

Use template and trace (12) cat paw prints onto Steam a Seam™

Directions

Prior to starting this project, please check our website for any updates: www.clothworks.com

All seams are sewn with a ¼" seam allowance unless otherwise indicated

Construction:

1. Sew the 4" squares into (4) 9 patch blocks. Finished blocks will measure 10 ½" square, unfinished.
2. Arrange 9 patch blocks and panel squares as shown in the photo. Sew 9 patch blocks to Cat Panel blocks.
3. Fuse cat paw prints in place and follow product directions.
4. Sew the right side of the Inner Cuff piece (raw edge) to wrong side of pillowcase body
5. Measure quilt length and cut side borders to size. Sew & press. Measure quilt width and cut top & bottom border to size. Sew and press. Repeat for outer border.

Finish the quilt:

1. Layer top with batting and backing. Baste or pin, and quilt as desired.
2. Cut 4 strips of binding at 2 ¼" x WOF. Join end to end. Press seams open. Press strips in half lengthwise. Apply binding.



Cat Paw Print Appliqué Template, Actual Size