



BLUE SQUARE

# SYSTEM DESIGN REQUEST FORM

Tel: 1.800.277.4150 Fax:1.888.282.6955

Email: plans@bluesquaremfg.com

www.bluesquaremfg.com

NOTE: Plan formats accepted are CAD, PDF, Jpeg, Pool Studio

<b>Builder Information</b>	For Bid	For Const.	<b>Pool Owner Information</b>
Name: _____			Job #: _____
Address: _____			Name: _____
City: _____ State: ____ ZIP: _____			Address: _____
Sales person: _____			City: _____ State: ____ Zip: _____
Contact #: _____			Phone: _____
Email: _____			Email: _____

### Project Specifications

Equipment	System Type	Head Placement	Interior Finish	Plumbing
Filter type: DE Cart Sand	Q360	*Check all that apply*	Plaster	*Check all that apply*
Pump Type: HP	E360	Pool	Pebble	Pool/spa share equip
Variable Speed: Yes No	Step 360	Spa	Tile	Solar Heater
Eclipse Drain: Yes No **Show Location	V360	Basin	Fiberglass	Skimmer Quantity **Show location on plan
Abys Canister: Yes No	Fiberglass	Feature	Vinyl	Returns **Show Location on plan
Hydrostat Valve Yes No		Neg Basin*	Other	Eclipse Drain in Spa
Distance from Q360 Valve to skimmer:		*Requires own equip.		

Po

<b>Pool</b>	Area: _____	Per: _____	Gallons: _____	<b>Pool Size</b>	Length: _____	Width: _____
<b>Spa</b>	Area: _____	Per: _____	Gallons: _____	<b>Spa Size</b>	Length: _____	Width: _____

**Q360 Notes:**

- \* THE Q360 SYSTEM SHALL BE INSTALLED PER THE INSTRUCTION MANUAL AND POOL INDUSTRY CODES.
- \* INSTALLING COMPONENTS THAT ARE NOT A DIRECT PART OF THE BLUE SQUARE PRODUCT LINE WILL VOID THE WARRANTY.
- \* THE BLUE SQUARE SYSTEM SHALL BE INSTALLED PER THE ENGINEERED CAD DESIGN PROVIDED BY BLUE SQUARE MANUFACTURING. FAILURE TO DO SO SHALL RESULT IN VOIDING THE WARRANTY.
- \* CHECK VALVES ARE REQUIRED ON ANY RAISED SPA PORT AND RAISED WATER FEATURES USING THE Q360.
- \* JETS ON THE SAME ZONE CAN NOT BE SHARED BETWEEN TWO BODIES OF WATER THAT ARE SET AT DIFFERENT ELEVATIONS.
- \* IF THE SUCTION RUN IS GREATER THAN 40' THE REQUIRED PIPE SIZE SHALL BE 2.5".
- \* THE Q360 SYSTEM IS DESIGNED/ENGINEERED WITH GPM SPECIFIC REQUIREMENTS. THE ADDITION OF WATER FEATURES OR OTHER ACCESSORIES MAY REQUIRE AN INCREASE IN PUMP SIZE FOR GREATER WATER FLOW (GPM).
- \* THE REQUIRED PIPE SIZE FOR BLUE SQUARE COLLARS/HEADS IS 2". NO REAMING IS REQUIRED FOR THE COLLAR.
- \* "Y" PIPES ARE MANDATORY ON ALL PORTS THAT ARE DESIGNED TO DOUBLE FIRE.
- \* THE DESIGN PROVIDED IS FOR JET PLACEMENT & BANKING ONLY. IT IS THE RESPONSIBILITY OF THE BUILDER TO FOLLOW ALL SAFETY REGULATIONS. BLUE SQUARE SHALL NOT BE LIABLE FOR ANY DESIGN SAFETY VIOLATIONS.
- \* BLUE SQUARE CAD DESIGN SHALL BE RETURNED WITHIN 48 HOURS.
- \* NEGATIVE EDGE BASINS REQUIRE SEPARATE EQUIPMENT

**Builder Notes:** \_\_\_\_\_