

# COOLANT PLUS

## GLOBAL FLEET NF



### PRODUCT DATA SHEET

NITRITE FREE    PREDILUTED    50/50

Coolant Plus Global Fleet NF is a heavy duty, maintenance free, extended life coolant (ELC) that provides a service life of 600,000 miles without the need of extenders if properly maintained. The additive package contains extended life corrosion inhibitors based on organic acids (OAT) and provides maximum protection against damaging rust and corrosion in engine cooling systems. This product is NAPS-Free and does not contain nitrite, amine, phosphate or silicate. Coolant Plus Global Fleet NF is suitable for use in modern heavy-duty diesel engines and is ideal for use in mixed fleet operations. Such as highway, off-road, marine, agricultural, mining and construction equipment.

*\*This product can be purchased colored Red or Gold.*

### INDUSTRY STANDARDS

The inhibitor chemistry conforms to ASTM D6210, D3306 and TMC RP364. It is compatible with major coolant types for top-off and continual service.

Cummins	Peterbilt	International	Detroit Diesel	Kenworth	John Deere
General Motors	Freightliner	PACCAR	Mack Truck	Volvo	Caterpillar
MTU	MAN	Mercedes-Benz	Scania	Ford	

PHYSICAL PROPERTIES		
Antifreeze Glycols	mass %	45.0 min.
Corrosion Inhibitors	mass %	5 BV
Water	mass %	50.0 max.
Color	Red or Yellow	
Weight per gallon at 60° F-16° C	Approx. lbs/gal	8.9
pH	Approx. premix	8.0—9.0

%Antifreeze	Freezing Point		Boiling Point	
	°F	°C	°F	°C
40%	-9	-22	240	115
50%	-34	-37	265	129
70%	-84	-64	276	135

\*Boiling point shown using conventional 15 psi radiator cap.

Used antifreeze coolant in most states is not hazardous unless it contains more than 5 ppm of lead. We recommend that spent coolant never be disposed of by dumping into a storm sewer or onto the ground. Instead, contact Products Plus, Inc. about antifreeze recycling options.



**PRODUCTS PLUS**  
INCORPORATED

ANTIFREEZE | WINDSHIELD WASH | HEAT TRANSFER FLUIDS

Products Plus Inc.  
877-581-3755  
info@ppicoolant.com  
ppicoolant.com