## **NEMA Wiring Device Extensions**

20A extra hard usage cords with plugs and connectors resistant to moisture, chemicals, and environmental concerns so you can use indoors or outdoors.



ISO 9001:2008 Registered Company



## **Key Features and Benefits**

- Produced with SOOW cord
- Straight blade, locking, and wetguard devices available
- · Factory-tested
- · 15A, 20A, and 30A assemblies
- · Heavy-duty UL and CSA cable
- Excellent oil, water, abrasion, and UV resistance

Wetguard Locking Extensions					
Rating	Cable	NEMA			
20A, 125 VAC	12/3 SOOW	L5-20 Locking			
20A, 250 VAC	12/3 SOOW	L6-20 Locking			
20A, 125/250 VAC	12/4 SOOW	L14-20 Locking'			

## **Options**

- · Carrying strap
- · Custom lengths
- · Custom cable identification

SOOW 600V CABLE									
AWG	No. of Conductors	Stranding/Diameter	Nominal Insulation Thickness.	Nominal Jacket Thickness	Nominal O.D.	Approx. Weight lbs./1000'	Ampacity* 30°C Ambient Temp.		
12	3	65/30	0.045" (1.14 mm)	0.095" (2.41 mm)	0.59" (15.2 mm)	217	25.0 A		
12	4	65/30	0.045" (1.14 mm)	0.095" (2.41 mm)	0.64" (16.5 mm)	261	20.0 A		
*Ampacity – Free air measured; based on continuous duty at 90°C conductor temperature									

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

815 Conger St., Eugene, OR USA 541.344.7267 1.800.971.7201 sales@westernshelter.com www.WesternShelter.com ISO 9001:2008 Registered Company