



- The PRED1200UV combines the bacteria-killing power of germicidal UV technology with the air-cleaning performance of HEPA filtration.
- Variable speed airflow, with maximum rated airflow as high as 900cfm
- Roto-molded body components are made from UL94HB flame retardant resin with EPA-registered microbial growth and UV inhibitors
- Upright design includes a built-in transport dolly, non-marking rear wheels and front 360° swivel casters
- Can operate in tight spaces where horizontal operation is needed
- Power consumption of less than 3.5 amps @ 120VAC allows for daisy chaining multiple units per 15A circuit
- The PRED1200UV has been independently tested and certified in accordance with applicable UL and CSA safety requirements

CL-ACAB1200UV Specifications

Dimensions	22 x 24 x 42"	(55.88 x 61 x 106.68 cm)
Weight	73 lbs	(33.11 kg)
Electrical Rating	120 VAC 60 Hz 15A	
Maximum Airflow	300 - 900 CFM	
Operating Amps	3.5 amps or less	
Motorized Impeller	400 watt, auto reset, 60 Hz, single phase	
Sound Level at 5'	62-67 dBA on high speed	
HEPA Filter Efficiency	99.97% @ 0.3 microns	
Cabinet Material	Polyethylene Cabinet Made From UL94HB Flame Retardant Resin	
Prefilter access	Hinged "no tools" access door	
First Stage Prefilter	F621, 1" deep coarse particulate	
Second stage Prefilter	H502UVR, 2" deep UV-resistant pleated particulate	
HEPA Filter	H610C-99	
UV Lamp	UV415, 23-watt UVGI lamp	