

## ST-2060A

### 60W DELTA LED STREET LIGHT

**BEAM ANGLE:** Type III

**POWER SUPPLY:** Replaceable Driver

**LIFETIME:** ≥ 50,000hrs

**INPUT VOLTAGE:** AC100-277V ~ 50/60Hz

**POWER FACTOR:** >0.9

**OPERATING TEMPERATURE:** -13°F ~ +113°F



**IK08**

**Housing:** The body of Delta Street Light series is made of aluminum with an anti-corrosive coating to protect it in caustic environments, such as salt spray. The acrylic optical plate has a high-impact resistance, and the luminaire is sealed with resilient gasketing to prevent ingress.

**Mounting Options:** Available options include a 2-3/8" adjustable pole mount, as well as slip-fitters in order to adapt to other mounting requirements. Pole arms are not included.

**Electrical:** The Delta Street Light comes standard with a high-performance, replaceable driver that goes from 100-277V, power factor of 90%+. The Easy Interchange System (EIS) allows for simple and easy field replaceability of the driver.

**Warranty:** Five (5) year warranty on entire system. For more details on warranty conditions, please contact factory.

**Lumen Maintenance:** The lumen packages are rated for 50,000+ hours ( $L_{70}$ ).

**Certifications:** UL certified to UL1598.




With **EIS**

## ORDERING GUIDE

MODEL	WATTAGE	BEAM ANGLE	CRI	CCT	FINISH	VOLTAGE
ST-2	060A	T3	8		DB	U
	060A 60W (with EIS)	T3 TYPE III	8 ≥80	30 3000K 40 4000K 50 5000K	DB DARK BRONZE	U 100-277V

## DIMENSIONS



## ENERGY DATA

	POWER	LUMENS	EFFICACY
TYPE III DIST.	60W	7200 lm	120 lm/W

## PHOTOMETRICS

### TYPE III DISTRIBUTION

