

# LED Light Tech™ Instant Start Ballast Compatible LED Tube

LED Light Technology's Instant Start ballast compatible tube eliminates the need for rewiring and allows fixture to maintain original UL compliance. It is an ideal energy saving choice for existing linear fluorescent fixtures.



16.5 Watt U-Bent



2 Foot: 8.5 Watts

3 Foot: 10.5 Watts

4 Foot: 12 Watts

4 Foot High Output 16.5 Watts

## SPECIFICATIONS:

- L70: 50,000 hours
- CCT: 3000K, 3500K, 4000K, 5000K
- 1500-2150 lumens
- G13 base
- 160°
- CRI: 82
- 100-277 VAC

## FEATURES AND BENEFITS:

- Over 41% energy savings vs F32T8 electronic instant start systems
- No mercury allowing for non-hazardous waste disposal.
- Emits virtually no UV rays or IR
- Glass-free for safer working conditions
- 5 year limited warranty
- Instant on, no flicker or buzz
- Fits into existing linear fixtures
- Compatible with Instant Start ballasts eliminating the need for rewiring and allows fixture to maintain original UL compliance.
- Full light output in spaces with temperatures down to -22°F (-30°C)
- Perfect for applications with frequent "on/off" switching cycles
- Buildings that desire to be mercury free

**LED Light Technology, LLC**  
 1004 Bay Tree Lane  
 Duluth, Georgia 30097



Tele: 770-559-0750  
 Fax: 770-783-8097  
 www.LEDLightTech.com

**PRODUCT ORDER CODE:**

Product Order Code Example: LLT-40-T8-4-IB-16-4

LLT	40	T8		IB		
			<i>Length</i>		<i>Watts</i>	<i>CCT</i>
			U= U Bend		8	
			2		10	3=3000
			3		12	4=4000
			4		16	5=5500

