



## Product Specifications / Technical Data

### Collection Name: Pride

Effective: June 22, 2016

Composition:	Phthalate-Free Virgin Vinyl
Size (inches / mm):	7.08" x 47.24" (179.83 x 1199.89mm)
Gauge:	1/8" (3.0mm)
Wear Layer:	20mil (.5mm)
Finish:	G88 Advanced Coating System
Edge:	Square
Sq.Ft. / Piece:	2.32
Sq.Ft. / Carton:	34.88
Pieces / Carton:	15
Cartons / Pallet:	50 (1,744 sq.ft.)
Pallets / 53' Truck:	22 (38,368 sq.ft.)
Weight / Carton:	34.44lbs
Weight / Pallet:	1,768lbs
Limited Warranty:	Lifetime Residential 15 Year Commercial

#### Testing

ASTM F1700 – Product Classification:	Class III, Type B, Embossed Surface Meets and exceeds passing requirements
ASTM E648 – Radiant Panel (Critical Radiant Flux-Fire Rating Flaming Spread):	Meets and exceeds passing requirements (Class 1)
ASTM D2047 James Machine – Coefficient of Friction (Slip Resistance)	Meets and exceeds passing requirements
ASTM F925 – Resistance to Chemicals:	Meets and exceeds passing requirements
ASTM F970 - Static Load Limit:	Meets and exceeds passing requirements (1,000 PSI-Modified)

#### Sustainability

Recycled Content:	No
ISO 9001 – Quality Management System:	Meets and exceeds passing requirements
ISO 14001 – Environmental Management System:	Meets and exceeds passing requirements
FloorScore® Certified:	Yes

[www.floornationusa.com](http://www.floornationusa.com)

1-855 3 RASKIN