

# Reuso

## CARPET TILE SPECIFICATIONS

CONSTRUCTION
PILE FIBER
TUFTING GAUGE
PILE HEIGHT
TOTAL CARPET WEIGHT
BACKING STRUCTURE
PILE TREATMENT
STANDARD MODULE SIZE

## EcoSquare®

Multi-Level Loop Texture  
100% Solution Dyed Nylon  
1/12 inch  
3,0 - 5,5 mm.  
4,010 gram/sq.m.

 **EcoSquare®**  
Reinforced Recycled Hard Back  
Stain and Soil Protection  
25 x 100 cm.

## EcoSoft®

Multi-Level Loop Texture  
100% Solution Dyed Nylon  
1/12 inch  
3,0 - 5,5 mm.  
2,895 gram/sq.m.

 **EcoSoft®**  
Recycled PET Cushion Back  
Stain and Soil Protection  
25 x 100 cm.

## PERFORMANCE

END USE CLASSIFICATION
CASTER CHAIR INDEX
DIMENSIONAL STABILITY
ELECTROSTATIC PROPENSITY
COLORFASTNESS TO LIGHT
INDOOR AIR QUALITY

BS EN 1307 Class 33 – Heavy Commercial  
BS EN 985 ≥ 2,4  
BS EN 986 < 0,15%  
AATCC 134 < 3 KV  
ISO 105 B02 Min L6  
GLP 1022

BS EN 1307 Class 33 – Heavy Commercial  
BS EN 985 ≥ 2,4  
BS EN 986 < 0,15%  
AATCC 134 < 3 KV  
ISO 105 B02 Min L6  
GLP 7543

## FLAMMABILITY

HOT METAL NUT
RADIANT PANEL TEST
SMOKE DENSITY
SURFACE FLAMMABILITY

BS 4790 Low Radius  
ASTM E648 Class 1  
ASTM E662 < 450  
ASTM D 2859 Passes

BS 4790 Low Radius  
ASTM E648 Class 1  
ASTM E662 < 450  
ASTM D 2859 Passes

## SOUND ABSORPTION

NOISE REDUCTION COEFFICIENT
-----------------------------

BS EN ISO 354 NRC 0.15 or higher

BS EN ISO 354 NRC 0,30 or higher




## CERTIFICATION




## INSTALLATION METHOD

25 x 100 cm.



Random Vertical Brick



Herringbone

Specifications are subject to normal manufacturing tolerances, and subject to change without prior notice.  
As in all quality carpets, colors are subject to dye lot variations.

## Headquarters

2054 New Petchburi Road  
Bangkapi, Huaykwang, Bangkok 10310 Thailand  
Tel +66 (0) 2314-5402, Fax +66 (0) 2318-3537  
www.carpetsinter.com, info@carpetsinter.com

