

Kaynemaile Mesh Fire Rating Information for BS EU

Below are tests completed for Kaynemaile mesh that may be relevant to your market.

Kaynemaile mesh and fixings meet USA NFPA and IBC code criteria for cladding and interior linings.

Kaynemaile mesh has achieved a **Group 1s** in the ISO 9705 room test with a SMOGRA of 0.5m2/s2. UL94 FR-V0 material at 3mm that is rated self-extinguishing.

Detailed information on the tests completed is below:

Mesh Performance Testing—KML22 65-FR

Test	Result
BS EU	
BS EN 13501-1:2007 + A1:2009	B-s1, d0
BS EN ISO 11925-2:2010	Compliant
BS EN 13823:2010 + A1:2014	Compliant
DIN 4102 part 1	Pass B1

For further information, refer to the <u>US Standards information sheet here.</u>

Disclaimer: It is the Buyer's responsibility to ensure that the Products are used in compliance with all building, fire codes, standards and laws. Kaynemaile shall have no responsibility whatsoever for any such compliance obligations (or any non-compliance).



PHONE: NZ +64 4 473 4989 AU Toll Free 1800 231 153 USA Toll Free 1855 387 5440 EMAIL: sales@kaynemaile.com

www.kaynemaile.com