

CITY OF JEFFERSON
Public Works Design Standards

Division 1

General Requirements



DIVISION 1 GENERAL REQUIREMENTS

1.1 GENERAL

- a. These Public Works Design Standards will be cited routinely in the text as the "Standards" or "PWDS".
- b. Wherever specific supplementary standards are indicated (ie. ASTM C-150), it shall be understood to mean the latest revision thereof.
- c. In interpreting these Standards, it is understood that: (1) if the context so requires: (a) the singular pronoun shall be taken to mean and include the plural pronoun; (b) the masculine pronoun shall be taken to mean the feminine and the neuter pronoun; and (2) all captions used therein are intended solely for the convenience of reference and shall in no way limit any of the provisions of these Standards.
- d. These Standards shall apply to all improvements within existing and proposed public right-of-way and public utility easements, to all improvements to be maintained by the City, and to all improvements for which the Development Code requires approval by the City. These Standards are to be guidelines for designers and developers in preparing their drawings and for City staff in reviewing drawings. Where minimum values are stated, greater values should be used whenever practical; where maximum values are stated, lesser values should be used whenever practical.
- e. Requests for variances to these Standards shall be based on topography, right-of-way, geography or existing physical conditions which impose an economic hardship on the applicant. Request must show that the variance meets the intent of the standards and will not compromise safety, impact other properties or cause an increase in maintenance.
- f. PWCS. The City currently has physical standards for the construction of streets and related work, sanitary sewers, storm drains and structures and waterlines which cover the standard construction requirements for these facilities within the City of Jefferson (*Oregon Standard Specifications for Construction – OSSC (ODOT/APWA)*, *subject to the material, equipment and provisions specified in these PWDS*). Standard Specifications are hereinafter referred to as Public Works Construction Standards (PWCS) and can be viewed at Jefferson City Hall or the Public Works Department, and can be purchased on-line through the link at:
<https://5207--62.myuplinxstore.com/franchise/index.htm>.
- g. In the case of conflicts between the text of these design standards and the standard details, or between the provisions of these design standards and the PWCS, the more stringent as determined by the Director of Public Works shall apply. Acceptable materials shall be as outlined in these Design Standards.

- h. All other utility improvements, including telephone, electrical power, gas and cable TV shall meet the current standards of the appropriate agency as well as City standards.
- i. Traffic Control Devices shall meet the standards of the current Manual on Uniform Traffic Control Devices, including Oregon amendments.
- j. All other work not covered by the above standards shall conform to the Oregon Standard Specifications for Construction – OSSC (ODOT/APWA), most recent edition.

1.2 PURPOSE

- a. The purpose of these Standards is to provide a consistent policy under which certain physical aspects of public utility design will be implemented. Most of the elements contained in this document are Public Works oriented and most are related to the development or platting process. However, it is intended that they apply to both public and private work designated herein.
- b. These Standards cannot provide for all situations. They are intended to assist but not to substitute for competent work by design professionals. The Standards are also not intended to limit unreasonably any innovative or creative effort which could result in better quality, better cost savings, or both. Any proposed departure from the Standards will be judged on the likelihood that such variance will produce a compensating or comparable result, in every way adequate for the user and City resident.
- c. The objective is to develop Standards which will:
 - 1) be consistent with current City Ordinances.
 - 2) provide design guidance criteria to the private sector for the design of public improvements within the City of Jefferson.
 - 3) provide public utility improvements designed in a manner to allow economical future maintenance.
 - 4) Develop minimal franchise and/or private utility standards for systems which will impact or potentially impact public streets and/or public utility systems.

1.3 ENGINEERING POLICY

- a. The engineering policy of the City of Jefferson requires strict compliance with Oregon Revised Statute 672 for professional engineers. The following requirements shall be applicable to the design of streets, grading plans, sanitary sewers, storm drain systems (including detention systems), and water distribution and storage facilities.
 - 1) All engineering drawings, reports, or documents designated herein shall be prepared by a professional Civil Engineer registered in the State of Oregon, or by a subordinate employee under his direction, and shall be signed by him and

stamped with his seal to indicate responsibility for them. Per interpretations issued by the OSBEELS Professional Practices Committee (December 2016), the design engineer shall seal and sign drawing sheets containing standard details (whether prepared by the City or other agencies), since the details are incorporated into the larger design which is under the responsible charge of the design engineer.

- 2) It shall be the Design Engineer's responsibility to review any proposed extension, modification or improvement of a public utility system with the City prior to final engineering and design work to determine any special requirements or whether the proposal is permissible. A preliminary review and/or approval of the drawings for construction for any project does not in any way relieve the Design Engineer of his responsibility to meet all requirements of the City or the obligation to protect life, health and property of the public. The drawings for any project shall be revised or supplemented at any time it is determined that the full requirements of the City have not been met. Furthermore, it shall be the Design Engineer's responsibility to review any and all standard details incorporated into the design (whether prepared by the City or other agencies), and verify that they are applicable to and appropriate for the proposed design.
- 3) Any engineer having submitted to the City false or inaccurate information of a material nature will be warned of their conduct, and the Oregon State Board of Engineering Examiners will also be advised.

1.4 DEFINITIONS AND TERMS

- a. Unless otherwise defined in these Standards, the following definitions, terms and abbreviations shall apply whenever used.
 - 1) ADA: Americans with Disabilities Act, including any amendments thereto, and all applicable federal rules and regulations implementing the ADA, including but not limited to the current version of the Public Right-of-Way Accessibility Guidelines (PROWAG).
 - 2) As-built Drawings: Drawings prepared by the Design Engineer, signed and dated by the city representative indicating the drawings have been reviewed and revised, if necessary, to accurately show all as-built conditions and construction details.
 - 3) City: The City of Jefferson, Oregon.
 - 4) Construction drawings: Drawings prepared by a registered professional engineer, including site plans, plan and profile views of utilities, cross sections, detailed drawings, etc., or reproductions thereof, approved by the City Engineer, which show the location, character, dimensions and details for the work to be done.

- 5) Definition of Words: Wherever, in these Standards, the words directed, required, permitted, ordered, designated or words of like importance are used, they shall be understood to mean the direction, requirement, permission, order or designation of the Director. Similarly, the words approved, acceptable, satisfactory, shall mean approved by, acceptable to, or satisfaction to the Director.
- 6) Design Engineer: The engineer licensed by the State of Oregon as a Civil Engineer under whose direction plans, profiles and details for work are prepared and submitted to the City for review and approval.
- 7) Director: The Director of Public Works of the City of Jefferson or his/her authorized representative.
- 8) Dwelling Unit: A single unit providing complete, independent living facilities for one or more persons, including permanent provisions for living, sleeping, cooking, eating and sanitation.
- 9) Easement: Areas along the alignment of streets, sidewalks or utilities which are outside of a dedicated street right-of-way. Easements to the City shall be prepared on standard City easement forms granting (to the City) access & easement rights along the utility line or facility, and formalizing the terms and conditions of the easement.
- 10) Multiple Family Dwelling: A building or portion designed thereof for occupancy by two or more families, living independently of each other.
- 11) Manufacturer's Name: Any manufacturer's name, specification, catalog number, or type used herein is specified by make in order to establish the standard requirements of the City. Other equivalent makes will be considered for approval, providing they are comparable with this established standard.
- 12) Owner: Any individual, partnership, firm or corporation by whom the Design Engineer has been retained or who, as a property owner, is making arrangements with the City.
- 13) Person: Individual, firm, corporation, association, agency or other entity.
- 14) Plans: See Construction Drawings.
- 15) Preliminary Review: Review of the construction drawings by the City as outlined in these standards. All City comments and provisions of these design standards must be addressed prior to final review and approval for construction.
- 16) PROWAG: See ADA.
- 17) PWCS: Public Works Construction Standards, consisting of Oregon Standard Specifications for Construction (OSSC (ODOT/APWA)), subject to the

material, equipment and provisions specified in these PWDS. See also PWDS 1.1.f.

- 18) PWDS: Jefferson Public Works Design Standards, consisting of this manual.
- 19) Residential User: The owner, lessee, or occupant of a single dwelling unit in one structure.
- 20) Right-of-Way: All land or interest therein which by deed, conveyance, agreement, easement, dedication, usage, or process of law is reserved for or dedicated to the use of the general public free of all encumbrances, within which the City shall have the exclusive right to install and maintain streets and public utilities.
- 21) Roadway: All of that portion of the right-of-way used, for vehicle movement, which exists between the curbs or proposed curbs or proposed curb lines.
- 22) Single Family Dwelling: Any residential building designed to house one family.
- 23) Standard Details: The drawings of structures or devices commonly used on City work and referred to on the construction drawings. Also called Standard Plans.
- 24) Street or Road: Any public highway, road, street, avenue, alley, way, easement or right-of-way to be used for vehicle movement.
- 25) Substantial Completion: Substantial Completion is that degree of completion of the project's facilities and operating systems sufficient to provide the City and the public the full time, uninterrupted, and continuous beneficial use and operation of the work, and after (i) all required functional and acceptance testing has been successfully completed; (ii) all final building, plumbing, mechanical and electrical inspections required have been completed and any identified critical defective or incomplete work replaced or corrected; and (iii) all required record drawings and maintenance bonds have been submitted and accepted by the City. The terms "substantially complete" and "substantially completed" as applied to all or part of the work refer to Substantial Completion thereof.
- 26) Survey Cut Sheets: Sheets of tabulated survey data, indicating stationing, structures, fittings, angle points, beginning of curve, points on curve, end of curves, staking offset, various elevations and offset utility cuts.
- 27) Traveled Way: That portion of the roadway for the movement of vehicles, exclusive of shoulder and auxiliary lanes.
- 28) UGB: Urban Growth Boundary.

1.5 LOCATION OF UTILITIES WITHIN RIGHT-OF-WAY OR EASEMENT

- a. The standard details indicate the general required location for each utility within the public right-of-way.
- b. Installation of franchise or private utilities in a common trench with public water, sanitary sewer or storm drain mainlines is prohibited. A minimum of 3 feet of horizontal clear separation must be maintained between public and private or franchise utilities except at crossings, as well as between water or fire service lines and private or franchise utilities. Franchise utilities or private utilities shall not be placed in City utility (ie. water, sewer or storm) easements, unless specifically directed in writing to do so by the Public Works Director, subject to separation requirements in excess of minimums as dictated by Public Works.
- c. Utility service companies proposing to install major utility systems larger than typically required to serve local users and which cannot conveniently be relocated in the future will be required to prepare detailed drawings showing how the proposed system can be installed within the right-of-way without conflicting with existing or proposed City utilities. Drawing requirements may include but not be limited to plan and profile of proposed systems based on a detailed topographic survey.
- d. Utility/Infrastructure Modifications Required Due to Changes on Private Property.
 - 1) If changes are made to private property which requires modifications to and/or relocation of City utilities/infrastructure which is installed on private property (ie. changes including but not limited to changes in finish grade, changes in surface type, change in use of the property, construction of structures, etc.), such modifications and/or relocation shall be completed by the property owner or Developer at their sole expense, as directed by the City.
 - 2) When modifications to and/or relocation of City utilities/infrastructure are required due to changes on private property, such modifications and/or relocation shall comply with current City standards, and shall be reviewed and approved in accordance with these PWDS.

1.6 PROVIDING FOR NEW & FUTURE DEVELOPMENT

- a. All public improvements shall be designed as a logical part of the development of the surrounding area, as required or approved by the City Engineer and Public Works Director.
- b. Storm drain systems and sanitary sewers shall be sized to accommodate the entire drainage basin which they will ultimately serve.
- c. Utilities and street improvements shall be extended to the boundaries of the development (ie. to and through) so as to provide for future extensions to the adjoining

areas and prevent adjoining properties from becoming landlocked. In the case of utilities, this shall include extension to the far side of streets fronting or adjacent to the development as required to avoid work within or under these streets in the future.

- d. The City may require over-sizing of utility lines to accommodate future growth of the City.
- e. Where existing City utility lines do not adjoin the proposed development or the capacity of existing lines is inadequate, the developer will be required to extend new utility lines to the development as necessary, and extend them to provide for service to adjacent properties, at the developer's expense.
- f. Connection of Existing Utilities. Existing City utilities crossed, intercepted by or in the vicinity of new utility lines or facilities shall be connected to the new City utility system at locations as required by the City Engineer and Public Works Director. Existing City utility lines which are parallel with, or which are replaced or superseded by the new utility lines (as determined by the City), shall be abandoned or removed as part of the project (and existing facilities or structures served by the abandoned lines shall be connected to the new system as applicable), as required by the City Engineer and Public Works Director.
- g. Where existing roadway improvements do not extend to the proposed development or the existing roadways to the proposed development are not adequate to serve the development, the developer may be required to improve the roadways to the development, at the developer's expense.
- h. The requirement by City standards that offsite or oversized street and/or utility improvements must be completed "at the developer's expense" does not preclude the developer from applying under any SDC credit, oversizing reimbursement or reimbursement district procedures which may be authorized by the City Council.

1.7 TIME LIMITS FROM DRAWING APPROVAL TO CONSTRUCTION

- a. The Developer shall obtain a construction permit and begin construction within six (6) months from the time the construction drawings are approved by the City Engineer. If construction does not begin within this period, the approvals of the construction drawings shall be null and void. Renewal of the approval for the construction drawings may result in additional conditions to update standard details, meet new standards, changed conditions or new information discovered since the original approval.

1.8 PHASED DEVELOPMENT

- a. In the case of a development approved to be constructed in phases, the construction drawings and infrastructure constructed for each phase shall be capable of standing alone.
- b. Approval by the City of construction drawings for each phase of a phased development

shall be independent of the approval for all other phases.

- c. The intent of these requirements is that the time limits between approval of the construction drawings by the City and the time by which construction must begin shall apply to each phase independently.

1.9 REVIEW PROCEDURE

- a. Detailed provisions covering the review procedures and permitting requirements for street, site and utility construction are contained in Appendix G of these standards. The following is an overview of these requirements.
- b. Pre-design Conference: The developer and developer's engineer are required to schedule a meeting with the Director of Public Works and the City Engineer after land use approval and prior to preparing final design drawings of the proposed improvements.
 - 1) A minimum of 5 working days prior to the predesign meeting, it shall be the responsibility of the developer or the developer's engineer to provide the City Engineer with copies of the following:
 - a) Topographic surveys and base maps showing existing streets and utilities within and adjacent to the property (*limits as required by the PWDS*), and;
 - b) A plan or summary detailing how each of the planning conditions of approval (*ie. land use conditions*) will be satisfied (*as applicable*), and;
 - c) Scaled plan view drawings showing proposed street & utility (*water/sewer/storm*) alignments and improvement limits and conceptual layouts (*addressing the requirements of PWDS, the development code and planning conditions of approval*), and;
 - d) A current title report (which includes a list of all existing easements, restrictions, and other encumbrances on all property where construction will occur, including copies of deeds, easements or other restrictive documents referenced in that report), and;
 - e) Other information requested by the Public Works Director or the City Engineer.
- c. Three (3) sets of complete construction drawings shall be submitted to the City for preliminary review. Submittal requirements are as outlined herein, and shall include a unit price engineer's estimate acceptable to the City Engineer and any required review fees. Incomplete submittals will be returned without review.
- d. Upon completion of the preliminary review, the City will return one (1) set of drawings outlining the required revisions. In order to be entitled to further review, the applicant's

engineer must respond to each comment of the prior review. All submittals and responses to comments must appear throughout to be a bona fide attempt to result in complete drawings. Resubmittals shall consist of a minimum of three (3) sets of drawings.

- e. Franchise Utility Coordination by Developer's Engineer. Once the preliminary review has been completed by the City and required revisions made, the Developer's engineer shall circulate the drawings to all utility service companies within the City (and other agencies as applicable), and bring any conflicts to the attention of the City Engineer and Public Works Director.
- f. Prior to final approval of the construction drawings, all proposed drawings from utility service companies must be received and approved by the City. Approvals from other agencies with jurisdiction must also be received where applicable, including but not limited to the Oregon Health Authority – Drinking Water Services (OHA-DWS), Department of Environmental Quality (DEQ), Department of Transportation (ODOT), Marion County and railroads wherein each has jurisdiction.
- g. The applicant is responsible for the coordination with the various utilities and agencies during design and construction. The utilities and agencies may include those shown in the Appendix.
- h. Upon final approval of the drawings for a Type B permit, submit a minimum of ten (10) copies of the revised drawings to the City Engineer to be stamped as approved for construction (see also Appendix G for Type A permit requirements). Additional sets may be submitted for stamping at the developer's option. No changes shall be made between the final verification set of drawings approved by the City and the drawing sets submitted to the City to be stamped, without the express written approval from the City. Any unauthorized changes introduced into the final drawings submitted for stamping will invalidate the final drawing approval.
- i. Prior to issuance of the public utility construction permits, the Developer shall provide the City with the following:
 - 1) Copy of an approved (by City Attorney) Developer/City Construction Agreement signed and notarized by the Developer and the Developer's engineer.
 - 2) Any required permit fees.
 - 3) Recorded copies of all required off-site and on-site easements and right-of-way dedications, with the following exception. For subdivisions or partitions where all public utilities will be constructed prior to the recording of a final plat, the execution and recording of the on-site easement documents and on-site right-of-way dedications can be done in conjunction with the final plat.
 - 4) All easements documents (as well as ROW dedications, easement quit-claim deeds, or similar documents) shall include a legal description and a to-scale exhibit map (containing the information required under PWDS 1.11), and

easements to the City shall use the City's standard form. Legal descriptions and exhibit maps shall be submitted for City review and approval prior to recording.

- 5) Proposed Construction Schedule.
 - 6) Certificates of insurance, minimum limits as outlined in the Appendix. City of Jefferson and City Engineer shall be named as additional insured.
 - 7) Evidence of Workman's Compensation coverage from contractor performing the work.
 - 8) Any required Waiver of Remonstrance agreements.
 - 9) Any required performance bonds.
 - 10) Other submittals specific to this project, including any required approvals from applicable state agencies, such as DEQ (sewer & erosion control), OHA-DWS (water), DSL, ODOT, etc.
- j. Approval of plans by the City Engineer or Public Works for issuance of a City Public Works street/site/utility construction permit does not relieve the developer, contractor or engineer from obtaining any and all reviews and permits required under the building, plumbing or electrical codes that any portions of the work may be subject to, or from any requirements under County, ODOT or other agency permits or approvals required for the project.

1.10 CONSTRUCTION DRAWING SUBMITTAL REQUIREMENTS

- a. Survey: *All topographic surveys shall be based from an official benchmark acceptable to the City, and be based on the NVGD 1929 datum to match the FEMA flood map elevations. Existing elevation benchmarks that are based on the NAVD 1988 datum shall utilize the appropriate conversion factor to convert to the NGVD 1929 datum. All temporary benchmarks for construction purposes are to be based off accepted City benchmarks.*

Based on the NOAA VertCon website, the current conversion (for this area) from 1988 to 1929 datum is about 3.360 feet – see → http://www.ngs.noaa.gov/cgi-bin/VERTCON/vert_con.prl for specific conversions by location.

****All** designs subject to a Type B Public Works Permit shall be based off of a complete topographic survey, including but not limited to the following.

- 1) ****Surface features.**
- 2) ****Subsurface features.**
- 3) ****Existing utilities (public and private).**
- 4) ****Property lines & all survey monuments within or adjacent to the limits of the**

required topographic survey.

5) **Right-of-way lines & centerline monuments.

- b. Drawing Submittal: The drawing submittal shall include the following as applicable unless otherwise approved by the City Engineer. The following is a general overview of drawing requirements, but is not intended to be exclusive. All requirements of the individual divisions of the standards shall be satisfied.

Since projects subject to a Type B Public Works Construction Permit vary greatly in size and complexity, not all provisions in this section will apply to all projects. For instance, small projects in improved areas which do not involve any street improvements or extensions of water, sewer or storm drain mainlines will not need to provide profiles for these facilities. To assist the design engineer, the minimum elements required of all designs subject to a Type B Public Works construction permit are designated as summarized in the sentence below.

****The elements in this section 1.10 which are marked by an (**) are required to be included on the drawings for all projects subject to a Type B Public Works construction permit (see PWDS G.5).** All other elements not so designated are only required if the project involves improvements or infrastructure referenced in the non-designated paragraphs or sentences. If there are questions due to the unusual nature of a project, these should be discussed with the Public Works Director at the predesign conference (PWDS 1.9.b)

- 1) **Construction drawings shall be submitted on 22" x 34" blackline sheets unless otherwise approved by the City Engineer. All drawings submitted for review and/or approval shall be stapled and bound into sets.
- 2) **City plan review fees as required.
- 3) **Cover Sheet
- 4) **Overall drainage, utility and street lighting plan.
- 5) Site grading plan where applicable.
- 6) Plan and profile for the following public utilities:
 - a) Streets
 - b) Water as specified
 - c) Sanitary sewers
 - d) Storm drains
- 7) **Stamped storm drainage calculations, including storm drainage basin maps.

- 8) **Erosion control plan.
- 9) **Standard details shall be included on the construction drawings.
- 10) **A current title report which includes a list of all existing easements, restrictions, and other encumbrances on all property where construction will occur, including full copies of deeds, easements or other restrictive documents referenced in the title report.
- 11) **Recorded copies of all easements and right-of-way dedications required in conjunction with the project, with the exception noted under PWDS 1.9.h.3 for subdivisions or partitions where all public utilities will be constructed prior to the recording of a final plat. Easements shall be worded such that no trees, permanent structures or improvements including parallel fences shall be placed or constructed on the easement. Easements shall be a constant width between manholes, valves or other in-line structures. Easement width shall be based on the deepest portion of the line between such structures. See the Appendix for standard easement forms.
- 12) **Proposed utility plans from all franchise utilities (final review).
- 13) **Engineer's unit price construction cost estimate acceptable to the City Engineer or unit price bid results (preliminary and final review). Cost estimates shall include all work covered under the PWDS (*excluding work covered by buildings permits for structures*), and shall include line items for street lighting and franchise utility trenching & conduit, as well as trenching & installation of street lighting conduits, junction boxes and pole bases as applicable.
- 14) The submittal may also be required to include a traffic study and a traffic control plan.
- 15) **A written summary of all deviations from the PWDS requirements, and written justification for any variance requests (see section 1.11). It is the responsibility of the design engineer to submit a written request for any proposed deviations or variances from City standards.

c. General

- 1) **A title block shall appear on each sheet of the drawing set and shall be placed in the lower right-hand corner of the sheet, across the bottom edge of the sheet or across the right-hand edge of the sheet. The title block shall include the name of the project, the sheet title and number, the name of the engineering firm, engineer's stamp, date and revision blocks. Revision blocks shall be filled in on each drawing sheet containing revisions from previously submitted or reviewed drawings.
- 2) **A north arrow shall be shown on each sheet containing plan views and adjacent to any other drawing which is not oriented the same as other drawings

on the sheet.

- 3) **The scale shall be 1"=10', 20', 40' or 50' horizontal and 1"=2', 4' or 5' vertical for all drawings except structural or mechanical drawings. The scale of corresponding plan views and profiles shall be the same.
- 4) **In cases where streets or public utilities exist or will be reconstructed, plan view scales shall not exceed 1" = 20'.**
- 5) **Each plan, profile and detail shall be labeled under the drawing. The scale for the plan, profile, or detail shall be noted under the title. Details not drawn to scale shall be so noted.
- 6) **All detail drawings, including standard detail drawings, shall be included on the drawing sheets.
- 7) **A complete legend of all symbols used shall be provided at the front of each drawing set or on the appropriate pages. In general, existing utilities shall be shown with a lighter line weight than proposed utilities.
- 8) **Letter size shall not be smaller than 0.10-inch high.

d. Cover Sheet

- 1) The first sheet (Cover Sheet) of all drawing sets shall include the following as a minimum:
 - a) **Project name.
 - b) **Design Engineer's name, address, telephone and fax number, and email address/website.
 - c) **Developer's name, address and telephone number, and email address.
 - d) **Vicinity Maps showing the location of the project in respect to the nearest major street intersection and a minimum of 500 feet around the site.
 - e) **Legend including all symbols and line types used on the construction drawings.
 - f) **General construction notes matching format and content of notes in the Appendix. Where there is insufficient room on the cover sheet, the notes can be included on a subsequent sheet.
 - g) **Sheet index located near lower right corner.
 - h) Include a summary table listing the number of lineal feet of new public streets and public mainline utilities to be constructed. Do not include

existing streets or utilities that are being replaced as part of the project with the same length, or private streets or utilities. Do not include service laterals. Identify the length of new streets and/or utilities under County or ODOT jurisdiction separately from those under City jurisdiction.

- i) **The City Planning Department file or docket number shall be listed for projects which required land use approval.

e. ****Overall Drainage, Utility and Street Lighting Plan.**

- 1) The overall drainage and utility plan shall show the following as a minimum:
 - a) **The location and elevation of a National Geodetic Survey, United States Geological Survey, State Highway, Marion County or City of Jefferson bench mark which the elevations shown are based shall be shown or noted. Temporary bench marks on or near the project site shall also be shown.
 - b) **Right-of-way lines, property lines, easement lines (including those outside the project but intersecting or within 150 feet of the project boundaries).
 - (1) *This distance can be reduced with written approval from the Public Works Director, but in all cases shall extend to the far side of right-of-ways and show property lines and improvements on the far side of the street along the entire property frontage, as well as showing enough of the adjacent properties to clearly illustrate drainage patterns, setbacks and utility issues.*
 - c) **Show (& list the recording reference numbers of) all existing easements affecting the property (on-site & off-site), and provide callouts with blanks for the proposed new easements (the recording references for proposed easements are to be inserted at the as-built stage).
 - d) **Existing and proposed streets, curbs, sidewalks, handicap ramps and driveways within the project and within 150 feet of the project boundaries (*see exception allowed under 1.10.e.1.b.1 above*).
 - e) **Existing and proposed sanitary sewers, storm drains, waterlines and appurtenances within the project and within 150 feet of the project boundaries (*see exception allowed under 1.10.e.1.b.1 above*).
 - f) **Existing franchise and private utilities within the project and within 150 feet of the project boundaries (*see exception allowed under 1.10.e.1.b.1 above*).

- g) **Lot or parcel numbers, street names and other identifying labels (including tax lot and address numbers for all existing properties shown). New street names are subject to the approval of the City.
- h) **Location and description of existing survey monuments, including but not limited to street monuments, property monuments, section corners, quarter corners and donation land claim corners within or adjacent to the limits of the work area.
- i) **Public and franchise/private utilities and other facilities to be relocated.
- j) Street light and area light pole locations based on a photometric design acceptable to the City, subject to City location and maximum spacing standards.
- k) Methodology proposed for individual lot drainage. Direction of drainage arrows and the following letter legend shall be used:

Symbol	Lot drains to:
C	Curb
P	Piped Storm Drain
DB	Detention Basin
S	Subsurface Disposal
→	Flow Direction

- l) The location of all curb weepholes shall be shown.
- m) **Existing drainage patterns within the project and within 150 feet of the project boundaries (*see exception allowed under 1.10.e.1.b.1 above*).
- n) Floodplain, floodway and wetland boundaries, including floodplain elevation with FEMA map reference.

f. Site Grading Plan

- 1) A site grading plan is required for subdivisions, multi-family, commercial or industrial developments, and partitions involving street improvements or fills.
- 2) A site grading plan is required for projects subject to site design review, including all commercial, industrial, or multi-family developments.
- 3) The site grading plan shall show proposed finished grade and parcel corner

elevations, with the existing and proposed contours shown at maximum one (1) foot intervals and extended a minimum of 100 feet beyond the improvements. Extremely flat sites will require contour intervals closer than 1 foot as necessary to clearly illustrate proposed grading and drainage slopes and limits.

- 4) The site grading plan shall show all drainage systems and proposed erosion control facilities.

g. Drainage Calculations

- 1) **A summary of drainage calculations, including basin maps, shall be presented in a clear, concise and complete manner on the site grading or drainage plan sheets. These calculations shall address all runoff into the drainage system and downstream capacity. If required by the City, areas contributing flow to each inlet must be computed separately and each inlet with contributing area shall be designated and shown on an accompanying contour map work sheet.

h. Plan Views

- 1) General: **Information required on the overall utility plan shall be shown on the plan views as applicable, including tax lot & address numbers of all existing lots or existing parcels shown. In addition, the following shall be shown:
 - a) **Utilities and vegetation in conflict with the construction or operation of the street and public utilities. Vegetation to include trees greater than 6 inches in diameter and landscape plantings within the right-of-way and easement areas.
 - b) Public and franchise or private utilities to be relocated.
 - c) Match lines with sheet number references.
 - d) **All existing survey monuments within or adjacent to work areas.
 - e) Additional information as outlined below or as required by the City based on unique or unusual features of the project.
- 2) Streets (*plan view*)
 - a) Street stationing shall be tied to existing property corners, centerline of intersections, and/or existing street monuments.
 - b) **Location, alignment and stationing of **existing streets and proposed street centerline and curb faces. **Location of all curbs, driveways, edge of pavement, sidewalks, etc. shall be dimensioned from right-of-way centerline, easement boundary or other means so that its location is clearly defined.

- c) Bearing of all street centerlines.
- d) Horizontal curve data of street centerline and curb returns, including stationing of point of tangency and point of curvature, length of tangent, length of centerline curve, delta angle, radius point, and centerline radius.
- e) Location of existing and proposed street centerline monuments.
- f) Centerline stationing of all intersecting streets.
- g) Curb return plan view details (scale not to exceed 1" = 10', with all running slopes & cross slopes of sidewalks, pedestrian ramps & landings labeled) and separate curb return profiles (showing gutter grades) for all curb returns with pedestrian ramps, to demonstrate compliance with PROWAG requirements. Where centerline street grades and cross slope street grades of both intersecting streets is less than 1% (including through the entire intersection), the City Engineer may allow plans to show only top of curb elevations along curb returns at quarter-points on the curb return detail views.
- h) Location of the low points of street grades and curb returns.
- i) Crown lines along portions of streets transitioning from one typical section to another.
- j) Location, alignment & dimensions of all street frontage sidewalks, including sidewalks to be constructed with the project and sidewalks which are deferred to a future date. Sidewalks to be constructed with the project and those deferred to the future shall be clearly designated, and all required sidewalk easements shown & labeled.
- k) For residential projects or multi-tenant commercial projects, the location of CBU mailboxes shall be shown (location must be acceptable to the local postmaster), and the ADA access path to the CBU mailboxes must be designated per OSSC 1111, with a note designating that the CBU and the required ADA access path to the CBU must be constructed prior to City acceptance of the street improvements.
- l) Partial street improvements must be based on a full street design (ie. provide full design as if the entire street were being constructed as part of project, including design of sidewalks & driveway approaches, etc. on both sides), with the portion actually to be constructed as part of the project being clearly designated on the plans.
- m) For streets which are anticipated to experience significant truck traffic (as determined by the City Engineer or Public Works), and for driveways or access points which will accommodate truck traffic,

wheel path templates shall be included on the drawings to demonstrate that the proposed improvements allow vehicular turning movements without encroaching onto sidewalks or crossing curbs outside of the defined driveway or vehicular access path.

3) Storm Drains (plan view)

- a) ****Location, stationing and **size of **existing and proposed storm drains and appurtenances. Show drainage facilities upstream and downstream of the project as required to illustrate conditions affecting the design.**
- b) ****Drainage facilities located outside of public right-of-ways shall be stationed from the downstream end. For all manholes, catch basins, etc, located in or adjacent to streets, drainage facility stationing shall correspond to the street stationing.**
- c) Mainline stationing of all service tees.
- d) ****Location of all manholes, cleanouts, junction boxes, pipelines, ditches, etc. shall be dimensioned from right-of-way centerline, easement boundary or other means so that its location is clearly defined.**
- e) All manholes and other structures shall be numbered and stationed to facilitate checking the plan views with the profile.
- f) ****Alignment, size and depth at property line or easement line of proposed storm drain laterals.**

4) Sanitary Sewer (plan view)

- a) ****Location, stationing and **size of **existing and proposed sanitary sewers and appurtenances.**
- b) All sanitary sewers shall be stationed from downstream manholes to upstream manholes.
- c) ****Location of all manholes, cleanouts, pipelines, ditches, etc. shall be dimensioned from right-of-way centerline, easement boundary or other means so that its location is clearly defined.**
- d) Mainline stationing of all service tees.
- e) All manholes, cleanouts and other structures shall be numbered and stationed to facilitate checking the plan views with the profile.
- f) ****Existing City manholes numbers shall be used for all existing manholes or mainline cleanouts shown. Following acceptance by the**

City, each new sanitary sewer manhole and new mainline cleanout shall be identified on the as-builts with a number provided by the City.

g) **The following information shall be provided for all sanitary sewer service laterals.

- (1) Mainline stationing
- (2) Alignment
- (3) Size
- (4) Length of service lateral
- (5) Depth at property line or easement line
- (6) Distance ties to property corners
- (7) Location of property line cleanout.

5) Water Distribution (plan view)

- a) **Location, stationing and **size of **existing and proposed water mains and appurtenances.
- b) Each valve and fire hydrant shall be identified and stationed to facilitate checking the plan views with the profile.
- c) **Location of all waterlines and hydrants shall be dimensioned from right-of-way centerline, easement boundary or other means so that its location is clearly defined.
- d) Waterline stationing shall be independent of the street stationing.

i. Profile Views

- 1) General: Profile views shall conform to the requirements and show the information outlined under this section as applicable:
 - a) Profile views shall be to the same horizontal scale and on the same sheet as the corresponding plan view.
 - b) Match lines with sheet number references.
- 2) Streets (profile view)
 - a) Original ground & finish grade profile along the centerline and curbs as appropriate. For off-set or super-elevation cross-sections, both curbs shall be profiled. Ditch invert profiles shall be shown where curbs are

not to be constructed. Profiles at intersections or cul-de-sacs shall be extended to the back of the far side PUE as a minimum, and to the top/bottom of cut or fill slopes where applicable.

- b) Stationing, elevations and percent slopes for centerline or top of curb profiles.
 - c) Beginning point of all vertical curves, points of vertical intersection, end of vertical curve, length of vertical curve, K-value and design speed, and low point of vertical curve if a sag curve.
 - d) Projection of the profile of streets that may be extended or reconstructed in the future. The projected profile shall extend a minimum of 200 feet beyond the proposed work limits. The City may require profiles to be extended further where necessary due to topography or to demonstrate ability to tie to existing streets. Projected profiles shall be designed to be compatible with the restraints of the terrain.
 - e) The top of curb profiles for all cul-de-sacs, including vertical curves for any grade changes exceeding 1%, with a K-value not less than 3.
 - f) Separate curb return profiles (*showing gutter grades*) for intersection curb returns in accordance with requirements under PWDS 1.10.g.2.g. The location of all pedestrian ramps shall be indicated and labeled on the curb return profiles.
 - g) Unless otherwise approved or required by the City, cross sections showing existing and proposed finish grade shall be shown at 50 foot intervals to demonstrate that the proposed street grades match the surrounding grades and address drainage concerns, as well as to determine the need for slope easements, as well as at existing driveways or other access ways. Unless otherwise approved by the City in existing developed areas, the cross sections shall extend a minimum of 50 feet beyond the right-of-way line where existing cross slopes are less than five percent (<5%) and a minimum of 25 feet beyond the right-of-way line where existing cross slopes are greater than five percent (>5%).
 - h) Profiles for partial street improvements shall include information for both the turnpike construction (including ditch profiles as applicable), as well as future street profiles, including cross section profiles.
- 3) Storm Drain (profile view)
- a) Profile of existing and proposed ground surface along centerline of pipe, with rim and pipe inverts at each manhole, catch basin, etc.
 - b) Manholes and other appurtenances shall be numbered and stationed to match the corresponding plan view.

- c) Size, slope, pipe material and class, length of storm pipe and class of backfill between consecutive manholes, catch basins, junction boxes or cleanouts.
 - d) All existing or proposed public and franchise or private utilities crossing the profile and any existing utilities which potentially are in conflict with construction of the improvements.
 - e) Existing drainage facilities, including offsite facilities upstream and downstream which affect the design (ie. size and capacity of upstream and downstream system).
 - f) Profiles for ditch and creek flow lines shall be extended as appropriate to illustrate conditions affecting the design beyond the project, both upstream and downstream. Typical cross sections shall also be shown.
 - g) Where mainline storm cleanouts are approved for storm lines which will be extended in the future, plan and profile showing the alignment and depth of the anticipated future extension from the proposed cleanout to the next manhole or catch basin shall be included (without mainline grade breaks between structures).
- 4) Sanitary Sewer (profile view)
- a) Profile of existing and proposed ground surface along centerline of pipe, with rim and pipe inverts at each manhole.
 - b) Manholes and other appurtenances shall be numbered and stationed to match the corresponding plan view.
 - c) Size, slope, pipe material and class, length of sewer and class of backfill between consecutive manholes.
 - d) All existing or proposed public and franchise or private utilities crossing the profile and any existing utilities which potentially are in conflict with construction of the improvements.
 - e) Where mainline sewer cleanouts are approved (PWDS 4.16.b.1), plan and profile showing the alignment and depth of the anticipated future extension from the proposed cleanout to the next manhole shall be included (without mainline grade breaks between manholes).
- 5) Water Distribution (profile view)
- a) Waterline profiles shall be provided for all waterlines within existing right-of-ways or along alignments paralleled (within 15 feet) or crossed by existing public utilities. Waterline profiles will not be required for new waterlines within new right-of-ways unless required to prevent

conflicts with proposed utilities.

- b) Profile of existing and proposed ground surface along centerline of pipe, as well as existing and proposed pavement surface of adjacent streets (where applicable).
- c) Location of valves, fittings, fire hydrants and other appurtenances with all valves and fire hydrants numbered and stationed to match the corresponding plan view.
- d) Size, pipe material and class, depth of cover and class of backfill and surface restoration.
- e) All existing public and private utilities crossing the profile and any existing utilities which potentially are in conflict with construction of the improvements.

1.11 EASEMENTS, ETC.

- a. ****Utility easements to the City** (in a form acceptable to the City and conforming to the PWDS requirements) shall be provided and recorded for any City utilities outside of public street right-of-ways. The minimum utility easement widths and property line offset requirements are referenced in subsequent PWDS sections for Storm Drain, Sanitary Sewer and Water. Other recorded easements/instruments affecting City access and/or interests (*ie. fire lane easements, detention easements & maintenance agreements, grease interceptor maintenance agreements, etc.*) shall also be in a form acceptable to the City and conforming to the PWDS requirements. See also Easement Procedure Summary on cover page of Appendix D
- b. ****Legal Description & Exhibit Map.** All recorded easement documents shall include a legal description of the easement area and a to-scale exhibit map (*with the easement area clearly shown and labeled, and including all information/callouts required to illustrate the information contained in the legal description, including point of beginning, bearings and distances if applicable*), except for easements created by a plat, in which case the recorded easement documents may reference the easement as shown on the plat. Exhibit maps not drawn and plotted to scale, or not containing the information required above, will be returned for revision.
- c. ****Street Frontage PUE.** Easements shall include minimum eight (8) foot public utility easements (PUE) for franchise utilities along all lot lines fronting public or private streets, as well as easements for sidewalks, utility vaults, light poles, mail boxes, meter boxes, fire hydrants, lateral cleanouts, etc. that are not within the public right-of-way. Since new right-of-ways typically result in the back of sidewalk being close to the right-of-way line, PUEs shall include wording that they are a "*utility easement*", a "*public sidewalk easement*", as well as a "*waterline, sanitary sewer and storm drain easement to the City of Jefferson*".

- d. ****Private Easements.** Private utility easements a minimum of ten (10) feet wide (centered on the utility pipe and offset from common property lines) shall be provided for all private water, sanitary sewer and storm drains outside of public right-of-ways and outside the boundaries of the property being served. While the City does not dictate the specific form required for use on private easements noted above, the forms used shall include provisions that the easement cannot be extinguished without explicit written authorization from the City, and will not be extinguished by the doctrine of merger (unless the properties are consolidated into a single legal lot of record).
- e. ****Recorded copies of all required easements shall be submitted prior to start of construction, with the exception noted under PWDS 1.9.i.3 for subdivisions or partitions where all public utilities will be constructed prior to the recording of a final plat.**

1.12 VARIANCES TO DESIGN STANDARDS

a. Request for Variance to Specifications/Standards

- 1) Variances to specifications or standards may be requested as outlined below.
- 2) It is to be noted that if the requested variance involves public safety, the City will rule in favor of safety.
- 3) It is the responsibility of the design engineer to submit a written request for any proposed deviations or variances from City standards. Failure by the City to detect a deviation or required variance during drawing review does not constitute a default approval of said variance, unless the variance was requested in writing as outlined below and approved by the City.

b. Variance Process

- 1) **Submittal**
 - a) Requests for variance shall be submitted in writing to the City Engineer. This written request shall state the desired variance, the reason for the request and a comparison between the specification/standard and the variance as far as performance, etc.
 - b) Any variance of these Standards should be documented and referenced to a nationally accepted specification/standard. The use thereof shall not compromise public safety or intent of the City's Standards.

2) City's Review

a) The variance request shall be reviewed by the City Engineer who shall make one of the following decisions:

- (1) Approve as is,
- (2) Approve with changes, or
- (3) Deny with an explanation.

b) Approval of a request shall not constitute a precedent.

3) Appeal

a) Applicant may appeal the City Engineer's decision to the City Council.

c. Criteria for Variance of Specification Standards

1) The City Engineer may grant a variance to the adopted specifications or Standards when all of the following conditions are met:

a) Topography, right-of-way or other geographic conditions impose an economic hardship on the applicant and an equivalent alternative which can accomplish the same intent is proposed. Variances to self-imposed hardships shall not be allowed. The variance requested shall be the minimum variance which alleviates the hardship.

b) A minor change to a specification or standard is required to address a specific design or construction problem which, if not enacted, will result in an undue hardship.

c) An alternative design is proposed which will provide a plan equal or superior to these Standards. In considering the alternative, the City Engineer shall consider appearance, durability, cost of maintenance, public safety and other appropriate factors.

1.13 PRECONSTRUCTION CONFERENCE

a. Following approval of the civil/site/street/utility drawing package by applicable agencies with jurisdiction, a preconstruction conference shall be scheduled with the City before issuance of the public works construction permits. The purpose of the conference is to discuss the construction schedule and times of the civil/site/street/utility work which require coordination, as well as to provide the opportunity for parties from the construction team and various agencies/entities involved to meet and coordinate as may be necessary, and answer contractor questions regarding the work shown on the approved drawings.

- b. In addition to a City representative, the meeting is to include the following from the development team:
- Developer's representative.
 - Developer's engineer of record during construction.
 - Prime contractor.
 - Street/site/utility subcontractor (if different than the prime contractor).
- c. Agency & Utility Company Notification. The development team shall be responsible for notifying the franchise and private utility companies (as well as the County Public Works and ODOT if applicable) of the time and location of the preconstruction conference, and requesting that a representative of each agency and utility be present. The Developer may be required to submit proof of notification to the City prior to the preconstruction conference. Copies of notification letters or emails sent to the utility companies are acceptable.
- d. The developer, prime contractor and/or the street/site/utility subcontractor shall provide the following prior to or at the preconstruction conference.
- Overall bar-chart project schedule (for the street/site/utility work)
 - Listing of supervisory personnel and two emergency contact persons.
 - Materials testing lab (and outside inspection entity if applicable).
 - List of subcontractors & major materials suppliers to be utilized by the prime contractor and the street/site/utility subcontractor for work under the Public Works Permit.
 - Certificates of insurance from the contractor performing the site/street/utility work, minimum limits and format as outlined in PWDS Appendix E. The City and Westech Engineering (*as City Engineer*) shall be included as additional insured. The City is to be named as the certificate holder.
- e. Evidence of Workman's Compensation coverage from the contractor performing the site/street/utility work.

1.14 CONSTRUCTION OBSERVATION, INSPECTION & TESTING

a. General

- 1) All public construction associated with development shall be inspected or periodically observed by a professional engineer licensed in the State of Oregon (or a qualified individual under his supervision) as required in the Developer-City Construction Agreement. City projects may be inspected by Public Works or the City Engineer as applicable and as determined by the City.
- 2) An engineer whose firm, or any member of the firm, has a corporate, partnership or any form of real property interest in the development for which the improvements are required cannot be designated engineer-of-record. The engineer-of-record's relationship to the project must be solely that of a professional nature.

- 3) It shall be the policy of the City not to provide full inspection services for non-public funded public improvements, including public access parking lots and fire lanes.
- 4) It shall be the Developer's responsibility to provide an engineer to perform periodic inspection and/or construction observation services for improvements which are designed and permitted under these PWDS, at the developer's expense.
- 5) These inspection and construction observation requirements are not applicable to individual sidewalk, driveway or service lateral permits for single residences. If the project scale is such that the retention of an independent engineer-of-record is not warranted, the Developer may request that the City provide these services. If the City agrees to provide these services, the Developer shall be responsible to reimburse the City for any costs incurred for these inspection and/or construction observation services.

b. City Activities

- 1) Services provided by the City shall include:
 - a) Liaison between the engineer-of-record and the City;
 - b) Monitoring of work progress and performance testing as deemed desirable;
 - c) The performance of administrative and coordination activities as required to support the processing and completion of the project;
 - d) The issuance of stop work orders upon notifying the engineer-of-record and/or the Contractor of the City's intention to do so.
 - e) Operate all valves, including fire hydrants, on existing waterlines.
- 2) In addition, the City shall be notified a minimum of 48 business hours (2 business days) prior to the following tests and inspections so that a City representative may be present to witness the inspections or tests.
 - a) Streets
 - (1) Curb inspection;
 - (2) Subgrade testing or proof rolls;
 - (3) Base rock testing;
 - (4) AC pavement placement and testing;

b) Sanitary Sewers

- (1) Mandrel testing of mainlines;
- (2) Air testing of mainlines;
- (3) Vacuum testing of manholes;
- (4) Video inspection of mainlines;

c) Storm Drains

- (1) Mandrel testing of flexible pipe storm drains;

d) Water Distribution System

- (1) Pressure tests;
- (2) Disinfection (*see App. B notes for procedures*).
- (3) Bacteriological Testing (*see App. B notes for procedures*).

c. Developer's Engineer-of-Record's Activities

- 1) The engineer of record must be registered to practice engineering in the State of Oregon. Material testing which is not performed by the engineer-of-record must be accomplished by a recognized testing firm or another registered engineer.
- 2) ***The engineer must personally perform all activities marked by an (*) and must supervise all individuals performing other delegated activities.**
- 3) The following minimum activities are required of the developer's engineer-of-record:
 - a) *Execute a form accepting responsibility (ie. the Developer-City Construction Agreement):
 - b) *Attend preconstruction conference and ensure that approved construction drawings are distributed to contractor, subcontractors and franchise utility companies.
 - c) Obtain and use a copy of City-approved construction drawings and specifications during construction;
 - d) Coordinate to ensure that the City is notified 48 business hours (2 business days) before the start of construction or resumption of work after shutdowns, except for normal resumption of work following Sundays or holidays.

- e) Call to the City's attention within two (2) working days all drawing changes, material changes, stop work orders or errors or omissions in the approved drawings or specifications.
- f) Maintain records which contain at least the following information and submit copies to the City on a weekly basis:
 - (1) Any Site Visits during the previous week
 - (a) Date and time of site visits
 - (b) Weather conditions, including temperature
 - (c) A description of construction activities
 - (2) Statement of directions to change drawings, specifications, stop work, reject materials or other work quality actions;
 - (3) Public agency contacts which result in drawing changes or other significant actions;
 - (4) Perceived problems and action taken;
 - (5) Final and staged inspections (notify & coordinate with City to allow City representative to attend during regular business hours);
 - (6) Records of all material, soil and compaction tests.
- g) The engineer of record shall either (1) provide all surveying services necessary to stake the project prior to and during construction and as necessary to prepare as-built drawings when the project is complete, or (2) confirm that these surveying services are being provided separately (by the developer or by the contractor), all in conformance with City Standards.
- h) Review and approve all pipe, aggregate, concrete, A.C. and other materials submittals to ensure their compliance with City Standards, and provide any submittal review comments to the City Engineer and/or Public Works;
- i) *Approve all drawing or specification changes in writing and obtain City approval prior to the performance of the work;
- j) Provide periodic construction observations of construction activities as required to ensure end products meet City specifications;
- k) *Perform (or verify that they are performed) material, compaction and other tests required to ensure City specifications are met;
- l) Periodically check that curb, storm drain work and pavement grades are

- in substantial conformance with approved drawings;
- m) For pavement construction, perform the following stage construction observations and record the date that each is verified:
 - (1) Curbs are built to line and grade;
 - (2) Subgrade meets grade and compaction specifications;
 - (3) Base rock meets grade and compaction specifications;
 - (4) Leveling course meets grade and compaction specifications;
 - (5) Wearing course meets grade and compaction specifications.
 - n) For sanitary and storm drain construction, perform the following stage construction observations and record the date that each is verified:
 - (1) Sewers are installed to proper line and grade;
 - (2) Trenches are properly backfilled and compacted;
 - (3) Construction staking is adequate to ensure that the sewer is properly installed with respect to easement, right-of-way and property lines;
 - (4) Air testing and video inspections are performed according to standard procedures.
 - o) For grading, verify that the grading plan, as staked, will result in acceptable slopes along exterior property lines, proper onsite and offsite drainage, and erosion control.
 - p) File a completion report which contains:
 - (1) The original of the project completion certification verifying that the work under the Public Works permit was completed in substantial conformance with the approved construction drawings;
 - (2) A complete set of black-line as-built drawings for review by Public Works and/or the City Engineer;
 - (3) The results of storm, sewer and manhole tests, video inspections, waterline tests, material tests, compaction tests and soil analysis as applicable.
 - (4) Written verification that all installed ADA ramps, sidewalks and exterior pedestrian access routes (those covered under the

Public Works permit) comply with current ADA and City standards.

- q) Submit final reproducible as-built drawings conforming to the requirements outlined herein.

1.15 AS-BUILT DRAWINGS

- a. As-built drawings prepared by the design engineer (or engineer-of-record) are required whenever the work results in new or modified public improvements and shall describe all revisions to the previously approved construction drawings.
- b. The engineer-of-record shall utilize information from the Contractor's field record drawings, the engineer's field inspections, and the as-built survey as applicable to ensure that the as-builts accurately reflect as-built conditions.
- c. Unless otherwise approved by the City Engineer, as-built drawings for sanitary sewer and storm drains shall be based off of an as-built survey conducted by a land surveyor registered to practice surveying in the State of Oregon.
- d. Show all below grade franchise or private utility vaults and street crossing, as well as all above grade transformers, pedestals, etc.
- e. The location of all utility stubs shall be shown on the as-builts (sanitary sewer and storm) based on distance ties from two permanent points. The tie points shall be immovable structures, such as property pins, street monuments or the center of manholes.
- f. The new sanitary sewer manholes and/or mainline cleanouts will be assigned numbers by the City at the as-built stage. City sewer manhole numbers shall be shown on the as-built drawings in parenthesis next to the design manhole designation. If street names are changed, the new street name shall be shown on the as-built drawings in parenthesis next to the original design street names. Since the inspection reports, TV inspection reports, etc, will reference the design street names and design sewer manhole numbers, the as-builts need to retain the design information (in addition to showing the new City sewer manhole numbers and as-built street names) to allow reference to the construction report documents.
- g. The recording references for the easement documents for all existing or required easements shall be included on the as-built drawings, as well as recording references for construction deferral agreements, maintenance agreements, etc.
- h. Legible black-line copies of the as-built drawings shall be submitted to the City prior to the final walkthrough inspection and submittal of the final as-builts.
- i. Final As-Builts. Following the final walkthrough, submit approved as-built drawings on mylar or vellum to the City Engineer. Additionally, two paper sets of final as-builts

shall be submitted to Public Works and one set to the City Engineer.

- j. In addition to the mylar or vellum as-builts, a digital map shall be submitted to the City Engineer showing the final configuration of lot lines and right-of-way lines within or fronting the development. The drawing shall be in Autocad format, with lot lines and right-of-way lines each on separate layers. Other than lot lines and right-of-way lines, the only other information shown shall be limited to street names and the name of the development.

