

I Chain Connections

No. 193X Anchor Shackles Screw Pin Type

Hot dip galvanized steel - Screw Pin Type | Packed $\frac{5}{8}$ " and smaller – 10 per box. $\frac{3}{4}$ " and larger - bulk | Packed $\frac{5}{8}$ " and smaller - 10 per box; $\frac{3}{4}$ " and larger - bulk



Item No.	193X-3/16	193X-1/4	193X-5/16	193X-3/8	193X-7/16	193X-1/2	193X-5/8	193X-3/4	193X-7/8	193X-1
Size	$\frac{3}{16}$	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{7}{16}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$	1
Diam. Pin	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{7}{16}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$	1	$1\frac{1}{8}$
Weight per 100	5	12	19	31	49	74	144	219	340	530
Working Load Lbs.	240	330	572	990	1320	1650	2500	3740	5060	6600

No. 193 LR Anchor Shackles Screw Pin Type

Hot dip galvanized steel - Screw Pin Type | Load rated to meet Federal Specification RR-C-271a Type IV Class I | Packed $\frac{5}{8}$ " and smaller - 10 per box; $\frac{3}{4}$ " and larger - bulk



Item No.	193LR-3/16	193LR-1/4	193LR-5/16	193LR-3/8	193LR-7/16	193LR-1/2	193LR-5/8	193LR-3/4	193LR-7/8	193LR-1	193LR-1 1/8	193LR-1 1/4	193LR-1 1/2
Shackle Size	$\frac{3}{16}$	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{7}{16}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$	1	$1\frac{1}{8}$	$1\frac{1}{4}$	$1\frac{1}{2}$
Diam. Pin	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{7}{16}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$	1	$1\frac{1}{8}$	$1\frac{1}{4}$	$1\frac{3}{8}$	$1\frac{5}{8}$
Working Load Limit Tons	$\frac{1}{3}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{2}$	2	$3\frac{1}{4}$	$4\frac{3}{4}$	$6\frac{1}{2}$	$8\frac{1}{2}$	$9\frac{1}{2}$	12	17
Weight per 100	5	12	19	31	49	74	144	219	340	530	705	955	1725

No. 193S Anchor Shackles

Screw Pin Type | No. 304 Stainless Steel



Item No.	193S-3/16	193S-1/4	193S-5/16	193S-3/8	193S-1/2	193S-5/8	193S-3/4
Shackle Size	$\frac{3}{16}$	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{5}{8}$	$\frac{3}{4}$
Diam. Pin	$\frac{1}{4}$	$\frac{5}{16}$	$\frac{3}{8}$	$\frac{7}{16}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{7}{8}$
Working Load Limit Tons	5	12	19	31	74	144	219
Weight per 100	320	450	650	1000	1990	3050	4495

Chain Connections

No. 194LR Chain Shackles

Hot dip galvanized steel; Screw Pin Type | Drop forged to United States Federal specification RR-C-271a | Packed $\frac{5}{8}$ " and smaller - 10 per box; $\frac{3}{4}$ " and larger - bulk



Item No.	194LR-1/4	194LR-5/16	194LR-3/8	194LR-7/16	194LR-1/2	194LR-5/8	194LR-3/4	194LR-7/8	194LR-1
Shackle Size	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Diam. Pin	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1	1 1/8
Working Load Limit Tons	1/2	3/4	1	1 1/2	2	3 1/4	4 3/4	6 1/2	8 1/2
Weight per 100	12	19	31	49	74	144	219	340	530

No. 195LR Anchor Shackles

Hot dip galvanized steel; Round Pin Type | Load rated to meet Federal Specifications RR-C-271b Type IV Class 4



Item No.	195LR-3/16	195LR-1/4	195LR-5/16	195LR-3/8	195LR-7/16	195LR-1/2	195LR-5/8	195LR-3/4	195LR-7/8	195LR-1
Shackle Size	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Diam. Pin	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1	1 1/8
Working Load Limit Tons	1/3	1/2	3/4	1	1 1/2	2	3 1/4	4 3/4	6 1/2	8 1/2
Weight per 100	6	13	20	32	47	70	140	230	345	532

No. 267 "S" Hooks

Zinc Plated Steel | Available in Stainless Steel | Packed 50 per box



Item No.	267-1/16	267-1/8	267-5/32	267-3/16	267-1/4	267-5/16	267-3/8
Size Inches	1/16	1/8	5/32	3/16	1/4	5/16	3/8
Length Overall	5/8	1 1/8	1 1/4	1 3/4	2 1/4	2 5/8	3 1/8
Weight per 100	2	6	2	3 1/4	7	12	21

No. 383 Cold Shuts

Zinc Plated Steel



Item No.	383-3/16	383-1/4	383-5/16	383-3/8
Diameter Stock	3/16	1/4	5/16	3/8
Inside Lengths inches	15/16	1 3/16	1 3/8	1 1/2
Weight per 100	3	6	10	18

Quick Links | Chain Connections



All Quick Links are stocked from two manufacturers. We stock high quality quick links from France. Please be aware of which quick link your application requires. Quick Links are not to be used for overhead lifting. DO NOT OVERLOAD. Stay within the Working Load Limit (WLL).

No. 7350 Quick Links Zinc plated steel | For quick connection of chain, cable and wire rope.
No tools required. Easily tightened with fingers. Can be used over and over again. Has tensile of proof coil and BBB chain



Item No.	7350-3.5	7350-4.5	7350-5.0	7350-6.0	7350-8.0	7350-9.0	7350-10.0	7350-12.0	7350-14.0	7350-16.0
Trade Size	1/8	5/32	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8
Length Overall	1 3/8	1 9/16	1 7/8	2 1/4	2 15/16	3 1/8	3 1/2	4 1/8	4 3/4	5 1/2
Jaw Opening	3/16	7/32	1/4	9/32	3/8	7/16	1/2	19/32	11/16	3/4
Working Load Lt.	132	176	440	660	1540	1760	2400	2860	3300	4000
Weight per 100	1 3/4	2 1/2	4 1/2	8	17	23	31	51	80	124

No. 7351 Wide Jaw Quick Links
Zinc plated Steel | 7351-SF | 7351-ST



Item No.	7351-1/8	7351-3/16	7351-1/4	7351-5/16	7351-3/8	7351-7/16	7351-1/2	7351-9/16	7351-5/8
Trade Size	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8
Length Overall	1 3/16	2 7/16	2 3/4	3 7/16	3 3/4	4 1/16	4 7/8	5 9/16	6 5/16
Jaw Opening	3/8	1/2	9/16	11/16	3/4	23/32	15/16	1 1/16	1 1/8
Working Load Lt.	200	440	770	1430	1760	1760	2755	4410	5510
Weight per 100	2 1/4	5 1/2	9	20	26	26	59	92	139

No. 7360 Delta Shaped Quick Links
Zinc plated Steel



Item No.	7360-1/8	7360-3/16	7360-1/4	7360-5/16	7360-3/8	7360-1/2	7360-9/16	7360-5/8
Trade Size	1/8	3/16	1/4	5/16	3/8	1/2	9/16	5/8
Length Overall	1 1/4	1 9/16	1 7/8	2 3/16	2 3/8	2 15/16	3 3/8	3 11/16
Height Overall	1 7/16	1 7/8	2 3/16	2 7/8	3 1/16	4 1/8	4 13/16	4 7/16
Jaw Opening	3/16	1/4	9/32	13/32	7/16	19/32	21/32	3/4
Working Load Lt.	155	330	550	1210	1540	2425	3970	4850
Weight per 100	2	5	8 1/2	19	25	56	89	135

Quick Links | Chain Connections

No. 7370 Pear Shaped Quick Links

Zinc plated Steel | 7351-SF | 7351-ST | Available in Stainless Steel see page 11



Item No.	7370-1/8	7370-3/16	7370-1/4	7370-5/16	7370-3/8	7370-1/2	7370-9/16	7370-5/8
Trade Size	1/8	3/16	1/4	5/16	3/8	1/2	9/16	5/8
Length Overall	2 1/16	2 3/4	3 3/16	3 15/16	4 1/4	5 11/16	6 3/16	6 15/16
Height Overall	1 5/64	1 15/32	1 11/16	2	2 1/4	3	3 5/16	3 3/4
Jaw Opening	3/8	1/2	9/16	11/16	3/4	15/16	1 1/16	1 1/8
Working Load Lt.	125	265	440	1060	1320	1940	3175	4410
Weight per 100	2 1/2	6 1/2	11	23	31	71	105	158

No. 7380 Square Quick Links

Zinc plated Steel



Item No.	7380-7/64	7380-1/8	7380-5/32	7380-3/16	7380-1/4	7380-9/32	7380-5/16	7380-3/8	7380-7/16	7380-1/2	7380-9/16	7380-5/8
Trade Size	7/64	1/8	5/32	3/16	1/4	9/32	5/16	3/8	7/16	1/2	9/16	5/8
Length Overall	15/16	1 1/16	1 1/4	1 1/2	1 11/16	1 15/16	2 5/32	2 3/8	2 11/16	3 1/16	3 1/2	4 1/16
Height Overall	11/16	7/8	1	1 1/8	1 1/4	1 5/16	1 7/16	1 9/16	1 11/16	1 15/16	2 1/4	2 1/2
Jaw Opening	5/32	3/16	7/32	1/4	9/32	11/32	3/8	7/16	15/32	9/16	11/16	3/4
Working Load Lt.	85	155	220	330	550	880	1210	1540	1985	2425	3970	4850
Weight per 100	2	2 1/4	3 1/2	6	10	15	21	28	37	62	98	152

No. 660 Lap Links

Zinc plated steel | The quickest and most economical way to connect two pieces of chain—or chain to eyelet, snap, ring, etc.



Item No.	660-1/16	660-1/8	660-5/32	660-3/16	660-1/4	660-5/16	660-3/8
Diameter Stock	1/16	1/8	5/32	3/16	1/4	5/16	3/8
Inside Lengths inches	9/16	5/8	3/4	1	1 1/4	1 1/2	1 5/8
Weight per 100	3/4	1	2	4	8	14	21

No. 7400 Connecting Links

Zinc plated Steel, quenched & tempered



Item No.	7400-3/16	7400-1/4	7400-5/16	7400-3/8
Diameter Stock	3/16	1/4	5/16	3/8
Inside Length Inches	11/16	7/8	15/16	1 1/8
Weight per 100	4	9	11	20