

# T-130 SX

T-130 Trail/Enduro Suspension - 130mm



<b>Colour</b>	Magenta with Black/Lime
<b>Sizes Available</b>	XS,S,M,L
<b>Frame</b>	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm Boost dropouts, Shimano Direct Mount hanger
<b>Fork</b>	SR Suntour Aion LO-R 27.5" CTS, Air Spring, 130mm Travel, Tapered steerer and 15QR
<b>Rear Shock</b>	Fox Float DPS Performance, Black coating, Rebound Adjustment and 3pos Adjust Evol
<b>Headset</b>	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
<b>Rear Hub</b>	Alloy, Double Sealed Cartridge Bearing Hub, 12mm X 148mm Boost Through Axle, 32 Hole
<b>Front Hub</b>	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 100mm Through Axle, 32 Hole
<b>Spokes</b>	WTB 2.0mm, Black Sandvik Stainless Steel Spokes, Brass Nipples
<b>Rims</b>	WTB STp i29 TCS System, Tubeless Ready, 32 Hole
<b>Tyres</b>	WTB Trail Boss, TCS Light High Grip 27.5" X 2.25", 60TPI, Folding Front, Riddler, Light Fast Rolling TCS 27.5" X 2.25", 60TPI, Folding Rear
<b>Shift Levers</b>	Shimano SLX M7000, I-Spec B, 11 Speed, Black
<b>Front Derailleur</b>	N/A
<b>Rear Derailleur</b>	Shimano SLX M7000, Shadow Plus, 11 Speed, Direct Mount
<b>Cassette</b>	SRAM PG-1130 11-42, 11 Speed
<b>Chain</b>	Shimano HG60, 11 Speed
<b>Crankset</b>	RaceFace Affect, direct mount 28T, 11 Speed
<b>Bottom Bracket</b>	RaceFace BSA, 73mm
<b>Seatpost</b>	KS LEV-Integra, Dropper Post with KG remote, 30.9, 100mm travel
<b>Seat</b>	Whyte Custom, dual density, triple panel design
<b>Bar</b>	Whyte Custom Alloy, 15mm Rise, 760mm Wide
<b>Stem</b>	Whyte Gravity Stem, 40mm XS/S, 50mm M/L
<b>Grips</b>	Whyte Lock-on
<b>Front Brakes</b>	TRP Slate T4, Four Pot, I-spec, 180mm Rotor
<b>Rear Brakes</b>	TRP Slate T4, Four Pot, I-spec, 160mm Rotor, Internal Routing
<b>Brake Levers</b>	TRP Slate, I-Spec
<b>Pedals</b>	None

The T-130SX gets a huge upgrade for 2017 and now uses the SCR single chainring specific frame. This multi-award winning frame is combined with the new SLX M7000 series 1 by 11 group set from Shimano.

WTB STp i29 rims and TCS tyres give a Tubeless ready wheelset which, when combined with the SR Aion fork and Fox Float DPS double chamber rear shock, give the SX the ability to tame your favourite trails.

Internal routing keeps cables and hoses out of harm's way and with our new rubberised frame grommets it's totally water tight.

<b>Dropout Code</b>	DROPWHQ4SD
<b>Shock Stroke and Sag Setting</b>	63mm, Sag 16mm (25%) to 19mm (30%)
<b>Reducer Bush Widths</b>	22mm x 8mm, 35.5mm x 8mm
<b>Eye to Eye Length</b>	216mm
<b>Weight</b>	14.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
XS	67.0 +0/-1	74	571.7	331	761
S	67.0 +0/-1	73.7	591.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
XS	1116.5	420	30.9	100	368.3
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2