

T-130 RS

T-130 Trail/Enduro Suspension - 130mm



Colour	Matt Granite with Lime/Magenta
Sizes Available	S, M, L, XL
Frame	6061 T6 SCR Aluminium SCR Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp system, alloy symmetrical SCS rear Triangle, 148mm Boost dropouts, Shimano Direct Mount hanger
Fork	Fox Float Performance 34, 27.5", 130mm Travel with GRIP 3-Pos Damper, Tapered steerer, Black Coating and 110mm x 15mm Boost E-Thru Axle
Rear Shock	Fox Float DPS Performance, Black coating, Rebound Adjustment and 3pos Adjust Evol
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Upper Bearing
Rear Hub	Hope Pro 4 with StSt Bearings, 11 Speed Shimano Freehub, 12mm X 148mm Boost Through Axle, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm X 110mm Boost Through Axle, 32 Hole
Spokes	DT Champion 2.0mm
Rims	WTB STs i29, 29mm wide, Sleeved Joint, TCS Rims
Tyres	WTB Vigilante, Light High Grip TCS 27.5" X 2.3", 60TPI Folding Front, Trail Boss, TCS Light Fast Rolling 27.5" X 2.4", 60TPI Folding Rear
Shift Levers	Shimano XT M8000, I-spec II, 11 Speed
Front Derailleur	N/A
Rear Derailleur	Shimano XT M8000, 11 Speed, Shadow Plus, Direct Mount
Cassette	Shimano XT M8000 11-46, 11 Speed
Chain	Shimano XT HG600, 11 Speed
Crankset	RaceFace Turbine Clinch, direct mount 32T chainring, 11 Speed, 30mm alloy Boost axle
Bottom Bracket	RaceFace BSA, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm S, 50mm ML/XL
Grips	Whyte Lock-on
Front Brakes	Shimano XT M8000, 180mm Rotor
Rear Brakes	Shimano XT M8000, 160mm Rotor, Internal Routing
Brake Levers	Shimano XT M8000, I-spec II
Pedals	None

The T-130 RS features our SCR single ring specific frame with mega-stiff symmetrical chainstays. A full width main pivot increases torsional stiffness, extends bearing life and maximises suspension performance.

The T-130 RS beat all comers in the prestigious "2016 Trail Bike of the Year" award in the What Mountain Bike, and for 2017 this bike sees improvements in both the wheels and suspension, keeping it in front of the crowd.

Whyte hubs are laced to WTB STs i29 29mm wide rims with WTB high air volume tyres to allow you to exploit even more speed and fun out of the T-130's geometry. Suspension is handled by Fox, using Boost lowers and their all-new GRIP damper which brings World Cup winning suspension performance to the T-130 RS.

Dropout Code	DROPWHQ4SD
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.7Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	67.0 +0/-1	73.7	591.4	331	763
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1136.5	420	30.9	107	406.4
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6