

T-130C RS

T-130 Trail/Enduro Suspension - 130mm



Colour	Granite with Orange/Blue
Sizes Available	M, L, XL
Frame	Uni-directional Multi Monocoque Front Triangle with internal cable routing, Tapered Head Tube and Intergrip integrated seat clamp system with alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Pike RC, 27.5", 130mm Travel, Fast Black coating, tapered steerer and 10mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings
Rear Hub	Whyte Cartridge sealed bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	DT Swiss Champion 2.0mm
Rims	RaceFace ARC-30, 30mm wide, Welded Joint, tubeless ready
Tyres	Maxxis High Roller II TR, 27.5" X 2.3" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Crossmark II TR 27.5 X 2.2" EXO Sidewall protection, Folding Rear
Shift Levers	SRAM X01 Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
Chain	SRAM XX1 Eagle, Black, 12 Speed
Crankset	SRAM X1-1400 Eagle GXP, XSYNC 2 Direct Mount 34T Boost chainring, 12 Speed Alloy
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 15mm Rise, 760mm Wide
Stem	Whyte Gravity Stem, 40mm M, 50mm L/XL
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RS, 4 Pots, 180mm Rotor
Rear Brakes	SRAM Guide RS, 4 Pots, 160mm Rotor, Internal Routing
Brake Levers	SRAM Guide RS, MMX Matchmaker
Pedals	None

The T-130 C RS features our single ring specific Carbon frame. A full width main pivot that increases torsional stiffness, extends bearing life and maximises suspension performance.

SRAM's all-new Eagle X01 12 speed drive-train is used on the T-130 C RS. This evolutionary groupset gives a massive 10-50 gear spread cassette, allowing the chainring to be increased to 34t, giving both top and bottom range improvement.

RaceFace ARC-30, 30mm wide, welded joint, UST Tubeless rims are combined with Maxxis TR tyres to give exceptional levels of control. Boost 148mm rear and 110mm front hubs have 10mm wide flange spacing creating a stiffer wheel.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, 35.5mm x 8mm
Eye to Eye Length	216mm
Weight	13.2Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
M	67.0 +0/-1	73.5	611.1	331	766
L	67.0 +0/-1	73.3	631	331	776
XL	67.0 +0/-1	73.2	650.7	331	786
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
M	1156.5	420	30.9	115	431.8
L	1176.5	420	30.9	120	457.2
XL	1196.5	420	30.9	130	482.6