

805

Trail Hardtail - 800 Series - 120mm



Colour	Lime with Black/Denim
Sizes Available	S,M,L,XL
Frame	6061 Hydro Formed T6 Aluminium, Multi Butted, Tapered Headtube, Internal Cable Routing with BBX, Chainstay Post Mount Dropouts and Get A Grip seat clamp system
Fork	RockShox Recon Silver RL, 120mm Travel, Turn Key Lockout with Adjustable Rebound, Tapered Alloy Steerer with 100mm X 15mm Maxle
Rear Shock	N/A
Headset	FSA No. 57B Orbit ZS, Sealed Cartridge Bearing 1.5" Lower, 1 1.8" Caged Upper Bearings
Rear Hub	Alloy, Cup & Cone, Double Seal, 32 Hole
Front Hub	Alloy, Cup & Cone, Double Seal, 15mm X 100mm Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Stainless with Brass Nipples
Rims	WTB Asym i23 Rims with TCS System, Tubeless Ready, 32 Hole
Tyres	Maxxis Ardent Folding 27.5" x 2.25" Front, Maxxis Crossmark II Folding 27.5" x 2.25" Rear
Shift Levers	SRAM X-5, 10 Speed
Front Derailleur	SRAM GX, 10 Speed
Rear Derailleur	SRAM GX, Medium Cage, Type 2, 10 Speed
Cassette	SRAM PG-1020 11-36, 10 Speed
Chain	SRAM PC-1031, 10 Speed
Crankset	SRAM FC800, 22/36 compact double with Power Spline, 10 Speed
Bottom Bracket	SRAM Power Spline, 73mm
Seatpost	Whyte 20mm Offset, 30.9mm x 400mm, 6061 Alloy, 2 Bolt Clamp, Adjuster
Seat	Whyte Custom, Triple Panel Design
Bar	Whyte Riser Bar 15mm rise, 31.8mm, 720mm Wide
Stem	Whyte Custom, 45mm S, M, 60mm L & XL
Grips	Whyte Custom Lock-on
Front Brakes	SRAM Level, 160mm Rotor
Rear Brakes	SRAM Level, 160mm Rotor, Internal Routing
Brake Levers	SRAM Level
Pedals	Fibre Reinforced Composite Platform

The 800 Series frame is brand new for 2017, using the very latest Whyte geometry based around a longer top tube, a short stem and wide 720mm bar. The 800 series bikes are also built around a 120mm travel fork, which brings trail bike levels of performance.

The BBX internal cable routing keeps cables clean and clear of grime whatever the conditions, while Whyte's surefooted geometry will make you want to ride come rain or shine.

WTB TCS i23 Asym rims with Maxxis TR front and rear specific tyres combine to make a Tubeless Ready package, with enough grip to fully exploit the 800 series trail geometry.

Dropout Code	DROPWHRC
Shock Stroke and Sag Setting	N/A
Reducer Bush Widths	N/A
Eye to Eye Length	N/A
Weight	12.9Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.5	74	604	303.5	789
M	66.5	74	623	303.5	807
L	66.5	74	641	303.5	832
XL	66.5	74	660	303.5	861

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1148	435	30.9	115	406
M	1168	435	30.9	125	444
L	1189	435	30.9	135	482.6
XL	1208	435	30.9	145	533