

# 29-C TEAM

## Carbon Performance Hardtail 29er - C29 Series



|                         |   |
|-------------------------|---|
| <b>Colour</b>           | Matt Black with Orange/Grey   |
| <b>Sizes Available</b>  | S, M, L   |
| <b>Frame</b>            | Uni-directional Multi Mono-coque with DOX internal cable routing, Post Mount chainstay mounted disc brake and full carbon dropouts, Inter-Grip integrated seat clamp system |
| <b>Fork</b>             | Fox Float SC 32, 29", 100mm Travel with 3Pos-Adj FIT4 Damper, Kashima coating, Tapered steerer and 110mm x 15mm Boost E-Thru Axle   |
| <b>Rear Shock</b>       | N/A   |
| <b>Headset</b>          | FSA No. 42 Integrated, Orbit ZS Plus, 1 1/8" - 1 1/2" Sealed Cartridge Bearings   |
| <b>Rear Hub</b>         | Whyte XC-209-Carbon Team Wheelset, 32 StSt spokes, Whyte Cartridge bearing, XD Driver, Micro engagement freehub, 32 Hole  |
| <b>Front Hub</b>        | Whyte XC-209-Carbon Team Wheelset, 28 StSt spokes, Whyte Boost 15mm x 110mm Through Axle, 28 Hole   |
| <b>Spokes</b>           | Double Butted Black Stainless Steel   |
| <b>Rims</b>             | Whyte X-C-209-Carbon Team Uni-Directional High-Modulus Carbon, 23mm wide, Tubeless Ready  |
| <b>Tyres</b>            | Maxxis IKON TR, 29" X 2.2" 120TPI, 3C(Maxx Terra) Folding Bead, EXO Sidewall protection   |
| <b>Shift Levers</b>     | SRAM XX1 Eagle, MMX Matchmaker, 12 Speed  |
| <b>Front Derailleur</b> | N/A   |
| <b>Rear Derailleur</b>  | SRAM XX1 Eagle, 12 Speed  |
| <b>Cassette</b>         | SRAM XG Eagle XG-1295 10-50, 12 Speed   |
| <b>Chain</b>            | SRAM PCXX1 Eagle, 12 Speed  |
| <b>Crankset</b>         | SRAM XX1 Eagle, XSYNC 2 direct mount 34T chainring, 12 Speed  |
| <b>Bottom Bracket</b>   | SRAM GXP Team, 73mm   |
| <b>Seatpost</b>         | RaceFace NEXT, Matt UD Carbon, 30.9mm x 400mm, 2 bolt clamp   |
| <b>Seat</b>             | Prologo Custom X-Zero, Ti Rail  |
| <b>Bar</b>              | RaceFace NEXT, Matt UD Carbon, Flat Bar, 31.8mm, 720mm Wide   |
| <b>Stem</b>             | Whyte Custom, -6 Degree, 70mm S, 80mm M & L   |
| <b>Grips</b>            | Whyte Lock-on, EVA Light-weight Foam  |
| <b>Front Brakes</b>     | SRAM Level Ultimate, 180mm CLX 2-piece Rotor, StSt hardware   |
| <b>Rear Brakes</b>      | SRAM Level Ultimate, 160mm CLX 2-piece Rotor, StSt hardware, Internal Routing   |
| <b>Brake Levers</b>     | SRAM Level Ultimate, MMX Matchmaker   |
| <b>Pedals</b>           | N/A   |

With the best of everything, including the all-new, Fox SC 32 fork with Boost and Kashima coating, Whyte in-house Carbon wheels and Raceface NEXT finishing kit, this is a ready "out of the box" race bike.

The 29-C Team comes with the all new SRAM XX1 Eagle 1 by 12 drive train. This massive spread of rear sprockets gives the range to increase the front chainring to a 34T, giving even more speed at the top end with no compromise on your climbing gear.

Using our undersize/oversize chassis design for outstanding power transfer and pin sharp tracking, combined with fatigue reducing compliance, this is a high-speed bike you can ride all day.

|                                     |          |
|-------------------------------------|----------|
| <b>Dropout Code</b>                 | DROPWH20 |
| <b>Shock Stroke and Sag Setting</b> | N/A      |
| <b>Reducer Bush Widths</b>          | N/A      |
| <b>Eye to Eye Length</b>            | N/A      |
| <b>Weight</b>                       | 9.6Kg    |

| Size | Head Angle | Seat Angle | Top Tube  | BB Height | Stand Over |
|------|------------|------------|-----------|-----------|------------|
| S    | 69.3       | 72.8       | 612.2     | 304       | 789        |
| M    | 69.3       | 72.8       | 627       | 304       | 809        |
| L    | 69.3       | 72.8       | 640.8     | 304       | 844        |
| Size | Wheelbase  | Chain Stay | Seat Post | Head Tube | Seat Tube  |
| S    | 1117.3     | 437.5      | 30.9      | 100       | 406        |
| M    | 1127.9     | 437.5      | 30.9      | 110       | 444.5      |
| L    | 1144.9     | 437.5      | 30.9      | 120       | 495.7      |