

G-160 RS

G-160 Gravity Enduro Suspension - 160mm



Colour	Matt Granite with Orange/Grey
Sizes Available	S, M, L
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Lyrik RC, 27.5", 160mm Travel, Fast Black coating, tapered steerer and 110mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Debonair, RT3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	Whyte Cartridge sealed bearing, 12mm X 148mm Boost Through Axle with Micro Engagement 6 Pawl XD Driver Free Hub, 32 Hole
Front Hub	Alloy, Double Sealed Cartridge Bearing Hub 15mm x 110mm Boost Through Axle, 32 Hole
Spokes	WTB 2.0mm, Black Sandvik Stainless Steel Spokes
Rims	WTB STs i29 Rims with TCS System, Sleeve Joint, Tubeless Ready
Tyres	Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall protection Rear
Shift Levers	SRAM X01 Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM X01 Eagle, 12 Speed
Cassette	SRAM XG-1295 Eagle 10-50, 12 Speed
Chain	SRAM XX1 Eagle, Black, 12 Speed
Crankset	SRAM Decendent Eagle GXP, XSYNC 2 direct mount 32T chainring, 12 Speed, Carbon
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150/170mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	Whyte Custom Alloy, 35mm bar bore, 15mm Rise, 780mm Wide
Stem	Whyte Gravity Stem, 40mm
Grips	Whyte Lock-on
Front Brakes	SRAM Guide R, 4 Pots, 180mm Rotor
Rear Brakes	SRAM Guide R, 4 Pots, 180mm Rotor, Internal Routing

The G-160 RS features SRAM's all new Eagle 12 speed drive-train. With its huge 10-50 gear range, it gives the rider all the climbing and trail riding gears needed to save enough energy for more fun on the way back down.

The RS is loaded with the very latest developments in Trail/Enduro bikes, WTB i29mm rims combined with Maxxis TR front and rear specific tyres help to give neutral handling without too much drag. RockShox suspension gives the rider the very best enduro package available.

This bike is ready for anything you want to throw at it, from hard-core trail riding to Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm
Weight	14.3Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	340.5	805.5
M	66.0+0/-1	74.5	636.6	340.5	813.5
L	66.0+0/-1	74.3	655.9	340.5	820.5
Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2