

G-160 WORKS

G-160 Gravity Enduro Suspension - 160mm



Colour	Matt Burnt Orange with Black/Blue
Sizes Available	S, M, L
Frame	6061 T6 SCR Aluminium Front Triangle with Tapered Head Tube and Intergrip integrated seat clamp, ISCG 5 guide mounts, alloy symmetrical SCR rear Triangle, 148mm Boost Dropouts
Fork	RockShox Lyrik, RCT3, 27.5", 160mm Travel, Fast Black coating, tapered steerer and 110mm X 15mm Boost Maxle
Rear Shock	RockShox Monarch Plus Debonair, RC3, Fast Black coating, Adjustable Rebound and Compression
Headset	FSA No. 57E Orbit ZS, 1.5" Cartridge Sealed Lower Bearing and 1 1/8" Cartridge Upper Bearing
Rear Hub	SRAM Roam 60, 12 x 148mm Boost Through Axle
Front Hub	SRAM Roam 60, 15 x 110mm Boost Through Axle
Spokes	SRAM Roam 60, StSt Butted
Rims	SRAM Roam 60, 30mm wide carbon Hookless rims, Full UST Rims
Tyres	Maxxis High Roller II TR, 27.5" X 2.4" 60TPI 3C(Maxx Terra) Folding Bead, EXO Sidewall protection Front, Maxxis Minion SS, 27.5" X 2.3" 60TPI Dual TLR, Folding Bead, EXO Sidewall protection Rear
Shift Levers	SRAM XO1 Eagle, MMX Clamp, 12 Speed
Front Derailleur	N/A
Rear Derailleur	SRAM XO1 Eagle, 12 Speed
Cassette	SRAM XG-1295 10-50, 12 Speed
Chain	SRAM XX1 Eagle, Black, 12 Speed
Crankset	SRAM XO1 Eagle GXP, XSYNC direct mount 34T Chainring, 12 Speed Carbon
Bottom Bracket	SRAM GXP Team, 73mm
Seatpost	RockShox Reverb Stealth 125/150/170mm, 30.9mm, MMX
Seat	Whyte Custom dual density, triple panel design
Bar	RaceFace SIXC Carbon 35mm Oversize, 20mm rise, 800mm wide
Stem	RaceFace Turbine 35mm Oversize, 32mm long
Grips	Whyte Lock-on
Front Brakes	SRAM Guide RSC, 4 Pots, 200mm Rotor
Rear Brakes	SRAM Guide RSC, 4 Pots, 180mm Rotor, Internal Routing

This is the bike our Gravity Enduro Team race on, and as such, it's got the best of everything, from SRAM, RockShox, RaceFace, Maxxis, and of course, Whyte.

This bike is ready for anything you want to throw at it, from hard-core trail riding to EWS Enduro racing. Full complement bearings are used throughout the design, giving this bike exceptional durability in the harshest UK conditions.

The 2017 frame geometry progresses even further as our Race Team experience is back-fed into our development programme.

Dropout Code	DROPWHQ4SR
Shock Stroke and Sag Setting	63mm, Sag 16mm (25%) to 19mm (30%)
Reducer Bush Widths	22mm x 8mm, no hardware at the rear
Eye to Eye Length	216mm
Weight	13.5Kg

Size	Head Angle	Seat Angle	Top Tube	BB Height	Stand Over
S	66.0+0/-1	74.7	607.6	340.5	805.5
M	66.0+0/-1	74.5	636.6	340.5	813.5
L	66.0+0/-1	74.3	655.9	340.5	820.5

Size	Wheelbase	Chain Stay	Seat Post	Head Tube	Seat Tube
S	1181.7	425	30.9	95	406.4
M	1211.7	425	30.9	110	431.8
L	1231.7	425	30.9	120	457.2