

Virtu Wide Plank Flooring

VIRTU 2-LAYER

SPECIFICATIONS

Point of Origin	Manufactured in the USA
Species	Most commercially available domestic and imported species
Product Construction	2 layer construction; 100% wood components Face layer: Solid sawn Core layer: Baltic Birch Plywood, Exterior Adhesive
Thickness	Total thickness: 19 mm (3/4") Top layer: 4 mm (11/64") Substructure 15 mm, 12mm (13/32", 15/32")
Widths	Standard widths: 4"-8" wide Special order: custom widths
Lengths	Standard lengths: 3'-12' long Special order: longer available on request
Finish	Unfinished; custom finishing available
Density / Hardness	Varies by species
Moisture Content	6-8% moisture content
Grading	Standard grade: Clear and better, Select and better Special order: Custom grades available
Custom Construction	Custom thicknesses and widths available
Milling	Tongue and groove edges; end matched ends
Radiant Heat	Designed to be used in radiant heat applications
Formaldehyde Content	No added urea formaldehyde
Packaging	Bundled for easy handling; approximately 7-10 sq. ft. per bundle
Lead Time	For material in stock: . . . prompt For custom production: . . 3 to 4 weeks (specialty items may be longer)
Installation	In accordance with National Wood Flooring Association guidelines
Relevant LEED Credits	MR-Credit 5 (Regional Materials) For products that are extracted, processed and manufactured within 500 miles of the installation, for a minimum of 10% of total material value. MR 5.2 Value of regional materials is at least 20% of the total material value (contributing) IEQ 4.1 Low emitting adhesives (contributing) EQ 4.2 Low emitting finish (if selected) 1 point
Manufacturer	Virtu Wood Flooring 200 North Rt. 303, West Nyack, NY 10994 (866) 668-6200

