BRUSHING MACHINE

LAH1.11.1807.GB

LA-H



The LA-H small-scale brushing machine is designed for batch and continuous processing of small volumes of seeds or grain prior to cleaning and grading processes

The LA-H brushing machine is mainly used for separation of grass seeds sticking together as well as polishing, de-hulling or peeling of different seed and grain products.

For more technical information see the back page.

The LA-H brushing machine offers the below features:

- Feeding tray with open/close shutter.
- ° One-section exchangeable standard mantle.

- Rotating shaft with two internally adjustable brushes or steel beaters.
- ° Manually adjustable brushing degree.
- Collecting drawers for prime product and removed product.
- Dust suction unit for connection to aspiration spout on top of the machine.
- ° Inspection window.
- ° Start/stop switch.
- ° Drive motor with frequency converter.

The machine is of steel construction.

Options:

- Inlet with vibrator feeder (instead of feeding tray)
- ° Outlet pipes for transport of product to floor level
- ° Autotransformer for 110 V, 60 Hz

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions



WESTRUP A/S SOROEVEJ 21 DK-4200 SLAGELSE P: +45 58 52 25 64 F: 58 52 52 51 E: INFO@WESTRUP.COM

CVR NO. DK 42 51 40 12 WWW.WESTRUP.COM

BRUSHING MACHINE LA-H

TECHNICAL SPECIFICATIONS:

	LA-H
Motor V	1 x 230
Drive motor kW	0.75

DISTINGUISHING ADVANTAGES:

- Feeding tray with open/close shutter ensuring a dustfree operation of a wide range of products
- ° Easy overview of the process through inspection window
- Electrical controls for easy connection into a 230 V outlet; Autotransformer for 110 V also available
- ° Easy clean-down when changing from one product to another
- ° Low maintenance costs



westrup