

BRUSHING MACHINE

HA-600 / -800

HA3.18.1901.GB



The HA-600/-800 brushing machine is very suitable for grass seed installations, especially for splitting twin kernels

For capacity and all other specific information see the back page.

The HA-600/-800 brushing machine offers the below features:

- Inlet with screw.
- Three-section exchangeable standard mantle.
- Rotating shaft with internally adjustable brushes.
- One common outlet.
- Manually operated bypass system integrated in the machine.
- Connection dia. 100 mm on top of the machine for external aspiration.

- V-belt drive and motor.

The machine is of steel construction with the sides of waterproof laminated wood.

Options:

- Various kinds of brushes and steel beaters
- Arrangement for external adjustment of brushes
- End outlet
- Clamps for quick opening of the mantle
- Frequency converter [supplied separately for customer installation]
- Larger motor
- Inlet with steel beaters and larger motor [instead of inlet with screw], which is especially suited for HA-800 for grass seed [excl. integrated by-pass system]

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions

BRUSHING MACHINE HA-600 / -800

TECHNICAL SPECIFICATIONS:

	HA-600	HA-800
Size of mantle: dia. x length	600 x 1245	800 x 1245
Nylon brushes pcs.	4	4
Nylon brushes mm	0.9	0.9
Capacity t/h	1	1.5
Motor standard kW	5.5	7.5
Motor for grass seed kW	-	18.5

Capacity: estimate [guideline]: based on pre-cleaned rye grass.

DISTINGUISHING ADVANTAGES:

- Inlet with screw ensuring a controlled feed also of very tangled products
- Rotating shaft with many types of brushes or steel beaters ensuring a highly efficient treatment of a wide range of products
- Can be customized for handling grass seed
- Prepared for easy connection to an external aspiration system giving a dust free operation
- Easy clean-down when changing from one product to another
- Low maintenance costs

