



## Full Specifications

	LP-6	LP-8
Powered:		Yes
Amplifier Class:		D
Power Configuration:		Bi-Amped
LF Power:	40 W (Continuous)	60 W (Continuous)
HF Power:	40 W (Continuous)	40 W (Continuous)
Total Power:	80 W (Continuous)	100 W (Continuous)
LF Driver:	6.5" Woofer	8" Woofer
HF Driver:	1" Soft Dome Tweeter	1" Soft Dome Tweeter
Freq. Response: (-10 dB)	39 Hz - 25 kHz	37 Hz - 25 kHz
Frequency Range: ( $\pm 3$ dB)	47 Hz - 21 kHz	45 Hz - 21 kHz
Crossover:	1.5 kHz	1.8 kHz
Listening Distance (85 dB Continuous output,	2.2 Meters	2.8 Meters
Max SPL:	112 dB	114 dB
System THD (94 dB @ 1 M)	<3% 80 Hz - 1.7 kHz <2% above 1.7 kHz	<2.5% 80 Hz - 400 Hz <1.5% above 400 Hz
Unbalanced Inputs:		1 x RCA
Balanced Inputs:		1 x TRS 1 x XLR
TRS/XLR Input Sensitivity:		+4 dB
RCA Input Sensitivity:		-10 dB
HF Trim:		-2 dB, $\pm 0$ dB, +2 dB
LF Trim:		-2 dB, $\pm 0$ dB, +2 dB
Boundary EQ Settings:		Free space (On stands, away from walls) On Stands, within .5 meters of a wall Against a wall Meter Bridge Wall Mount On a desk, away from walls On a desk, within .5 meters of a wall
Enclosure:		Front Ported
Height:	14.125 Inches (35.9 cm)	16.5 Inches (48.2 cm)
Width:	8.75 Inches (22.2 cm)	10 Inches (36.8 cm)
Depth:	10.25 Inches (26 cm)	11.25 Inches (32.4 cm)
Weight:	15.54 lbs (7.01 kg)	19.8 lbs (9 kg)