



# **Rulebook TECH UPDATE**

## **Speedway Chassis Updates: Nerf Bar Design**

**EFFECTIVE DATE: 02/22/2018**

### **OLD Rule:**

#### **20.3.15: 0.75" Tubing Nerf Bars**

20.3.15.1: The overall length of the side nerf bar shall be a minimum of 22.00" bottom bar from center-to-center of mounting points and 12" top bar measured from the back side of the nerf bar closest to the rear tire and the rear of the kart in a straight line to where it attaches to the kart at the front.

20.3.15.2: Double high nerf bars are mandatory.

20.3.15.3: Main nerf bar members shall not be less than .750" by .065" wall thickness, cold rolled steel tubing or other material of equal or greater strength.

### **New Rule:**

#### **20.3.15: 0.75" Tubing Nerf Bars**

20.3.15.1: The overall length of the side nerf bar shall be a minimum of 22.00" from center-to-center of mounting points .

**20.3.15.2: Flat single bar nerf bars are not permitted.**

20.3.15.3: Main nerf bar members shall not be less than .750" by .065" wall thickness, cold rolled steel tubing or other material of equal or greater strength.

Please contact NKA with any questions.

---

Mike Burrell  
NKA Technical Director

**PO Box 2166 Noblesville, IN 46061  
Ph. 317.774.7021 Fx. 317.774.7029  
[www.nkaonline.com](http://www.nkaonline.com)**