



WARNING! DO NOT OVERFILL.
 PRESSURE NOT TO EXCEED 100 PSL
 DO NOT OPEN WHILE PRESSURIZED.
 INVERT AND RELEASE ALL AIR
 BEFORE LOOSENING COLLAR.

FOR USE WITH:

- ▀ FABRIC PAINT
- ▀ ACRYLIC PAINT
- ▀ OIL PAINT
- ▀ WATERCOLOR
- ▀ VARNISH
- ▀ ALCOHOL INK
- ▀ PRIMER
- ▀ ADHESIVE
- ▀ CLEANER
- ▀ WATER
- ▀ ANY OTHER LIQUID

Thin to the consistency of milk if necessary.

STEP 1

FILL CAN 1/3 FULL OF FLUID

STEP 2

INSERT VALVE GASKET [D] & VALVE [C], THEN SCREW ON COLLAR [B]


STEP 3

CHARGE WITH AIR USING ADAPT-AIR COUPLING [E]

INSERT ADAPT-AIR COUPLING [E] INTO VALVE ON CAN AND CONNECT HOSE. USE AIR COMPRESSOR OR BIKE PUMP TO PRESSURIZE CAN. REMOVE ADAPT-AIR COUPLING.

STEP 4

ATTACH SPRAY CAP [A] OR ANOTHER OF YOUR CHOOSING AND SPRAY



RUPERT, GIBBON & SPIDER, INC.
MANUFACTURERS OF JACQUARD PRODUCTS
 HEALDSBURG, CA 95448 | MADE IN THE USA
 WWW.JACQUARDPRODUCTS.COM | 800.442.0455
 CONFORMS TO ASTM D-4236