

# PRESIDENTIAL SHAKE TL®

- Three-piece laminated fiber glass construction
- Distinctive sculpted, rustic look
- 475 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty - group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Presidential Starter (required) and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

## Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018
  Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

#### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

## Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance:Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

• ICC-ES-ESR-1389 & ESR-3537

























## PRESIDENTIAL SHAKE®

- Two-piece laminated fiber glass construction
- Distinctive sculpted, rustic look
- 355 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty
  group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart<sup>™</sup> protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Presidential Starter (required) and hip and ridge accessory available (see details in back of brochure)
- Impact Resistant version available (Select colors\*\*)
- ENERGY STAR qualified version available: Presidential Solaris® Gold meets both solar reflectance and thermal emissivity requirements. (Select color\*\*\*)
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

## Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018
  Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3018
  Type 1
- ASTM D3161 Class F

#### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

## **Impact Resistance:**

 Presidential Shake IR is UL2218, Class 4 Impact Resistance (Select colors only)

## Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

#### **Quality Standards:**

• ICC-ES-ESR-1389 & ESR-3537