

DC-240: Value-Priced Direct-to-Card Printer Bundle



DASCOM's innovative technology allows the DC-240 to deliver more value to your work, generating more cards at the best possible value.

The DC-240 produces bright, high-resolution prints, with all the necessary supplies included in the box to get you up and running as soon as you receive the printer.

DASCOM security features help mitigate the chance that your organization's identification process is compromised. You can focus on other areas while the DC-240 handles the integrity of your identification processes.

Identification Card Printer with Bundled Solutions

- 300 image print ribbon and 100 cards included
- Free card editing software
- Productivity of up to 155 cards per hour
- Photo print quality
- 100 card feeder
- Obscure sensitive information from the used ribbon



New easy to load ribbon cartridge

DASCOM DC-240 Bundle Includes:

- DC-240 single-sided printer
- YMCKO ribbon (300 images)
- Cleaning set: cleaning card, roller and wipes
- 100 blank PVC cards (30 mil)

DC-240: Value-Priced Direct-to-Card Printer Bundle

| | |
|-----------------------------------|---|
| Print speed | YMCKO ribbon: 155 cards per hour K or W ribbon: 390 cards per hour |
| What's included in the box | 300 image YMCKO ribbon, 100 white PVC cards, cleaning kit, CardEditor software |
| Resolution | 300 dpi |
| Feeder capacity | Automatic input of 100 cards or manual feeding Output: 25 (front) + 75 (rear) and automatic tray selector |
| Card thickness | 10 - 50 mil in the automatic feeder, 0.25-1.25 mm |
| Printing method | Color dye-sublimation technology |
| Memory | RAM: 32MB, ROM: 2MB + 4MB |
| Processor | Integrated Circuit / STMicroelectronics |
| Graphics processor | FPGA / Lattice Semiconductor |
| Printing capacity | Photo-quality images |
| Safety features | Ribbon Erase, RFID protected ribbons, Printed Custom Watermark |
| Use conditions | Temperature: 32°-104°F, 0°- 40°C. Humidity: 20 - 65% |
| Storage conditions | Temperature: 23° - 158° F, -5° - 70°C. Humidity: 35 - 96% |
| Dimensions | 7.83 x 13.85 x 8.26 in, 199 x 352 x 209 mm (W x D x H) |
| Weight | 13.2 lbs, 6.2 kg |
| Warranty | 3 year |
| Printhead life | 20,000 YMCKO images |
| Drivers | Windows XP, Vista, 7, 8, 10, 11 (32 and 64 bits) |
| Power supply | 100-240 V, 50/60 Hz |
| Compatible cards | PVC, ABS, PET, PET-G, PC, Teslin; 85.6 x 53.98 mm (ISO ID-1 / CR-80 size) |
| Standard interface | USB 2.0, USB host |
| Card editing software | DASCOM CardEditor included. Printer can be used with other other card design software, or as a traditional Windows® printer |

DASCOM Americas
34 Lakeview Court
Verona, Virginia, 24482 USA
Tel: +1 (877) 434-1377
www.dascomamericas.com
info.us@dascom.com

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0
Fax: +49 731 2075-100
info@dascom.com
www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road
Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507
Fax: +852 2413 6047