

Hydrotech

Single Solution Systems For Multiple Water Problems

Many ground water supplies often have multiple problems that are not only an issue from an aesthetic standpoint but in terms of cost when pipes become clogged, fixtures stained and laundry discolored. Combination units use mixed beds of a variety of different medias to provide one solution for your water woes.

HIM Series - Hardness, Iron and Manganese

Rid your water of hardness minerals (calcium and magnesium) and enjoy soft skin, silky hair, spot free dishes and brighter laundry protecting your plumbing and water using appliances from scale build-up. Removing iron and manganese will keep fixtures from getting stained as well as removing the taste and smell.



Soft, Clean
Truly Refined
Water



Features:

- Exclusive NSF Certified electronic control valve (systems available with Hydrotech 89, 785, 565 and 765 control valves)
- User friendly LCD display with 48 hour memory back-up
- Fully adjustable cycles allow for the most efficient settings based on the specific water quality requirements
- NSF Certified fibreglass pressure tank
- High density polyethylene salt tank
- Brine safety valve for added overflow protection
- Plastic salt grid prevents salt bridging
- Unique precision turbine meter is incorporated in system bypass valve – saving space over 4" of floor space
- Time saving quick connect fittings on brine line, drain line (with O-ring seal) and power cord for fast and easy installations



89 valve

- True 1" porting for high flow rates up to 18" systems. Ideal for larger homes.
- Large Backlit LCD display screen with 4 line / 80 character touch pad screen.
- Seven Year Warranty



785 valve

- High flow rates up to 16" systems.
- Rotating 'No Touch' Information Display (i.e. Date last regenerate, volume remaining)
- Seven Year Warranty



565 valve

- Simple user friendly 2 line / 32 character display
- Rotating 'No Touch' Information Display (i.e. Date last regenerate, volume remaining)
- Seven Year Warranty



765 valve

- Simple electronics with index knob to manually initiate regeneration and select cycle position
- Five Year Warranty

Specifications	HIM-100	HIM-150	HIM-200	HIM-250	HIM-300
Factory Settings - Iron & Manganese					
Salt Used - Per Regeneration	12.0 lbs	18.0 lbs	24.0 lbs	30.0 lbs	36.0 lbs
Water Used - Regeneration	52.2 gal	74.4 gal	101.4 gal	130.5 gal	166 gal
Hardness Removal - Grains	30,000	45,000	60,000	75,000	90,000
Resin Quantity - Cubic Feet	1.0 ft	1.5 ft	2.0 ft	2.5 ft	3.0 ft
Tank Size	9x48	10x54	12x52	13x54	14x65
Media Loaded	Yes	Yes	No	No	No
Brine Tank Size (Inches)	BTR 18.1 x 34.5 BTS 15.0 ² x34.7	20.3 x 37.4	20.3 x 37.4	20.3 x 37.4	23.0 x 40.5
Salt Storage Capacity	BTS 240 lbs BTR 270 lbs	350 lbs	350 lbs	350 lbs	420 lbs
Flow Rate @ 15 psi Pressure Drop	11.0 gpm	11.2 gpm	12.2 gpm	12.4 gpm	12.6 gpm
Flow Rate @ 25 psi Pressure Drop	15.0 gpm	15.1 gpm	16.2 gpm	16.4 gpm	16.6 gpm
Back Wash Flow Rate	2.1 gpm	2.4 gpm	3.5 gpm	4.0 gpm	5.0 gpm
Shipping Weight	125 lbs	158 lbs	175 lbs	208 lbs	247 lbs
Regeneration Type	Co-Current / Down Flow				
Maximum Hardness	75 Grains Per Gallon				
Maximum Iron (Ferrous)	10 ppm				
Maximum Manganese	5 ppm				
Resin Type	Purolite® SST-60				
Plumbing Connections	Includes 3/4" 90° Elbows & 1" Straight NPT 89 model is 1" straights only				
Electrical Requirements	Input 120V 60 Hz - Output 12V 650mA				
Water Temperature	Min 39 - Max. 100° F				
Water Pressure	Min. 20 - Max. 125 psi				

Includes ResCare Feeder
Plus 1 Quart of Res Care



Hydrotech

A Division of



In the U.S.A. 1-877-288-9888

In Canada 1-877-288-9888

www.hydrotechwater.com

Regina, SK • Cambridge, ON • Carmel, IN • Fridley, MN • Pottstown, PA • Phoenix, AZ

Your Local Water Treatment Professional