

ZY-T SERIES

Volumetric LED Troffers



ZY-T4

Features:

Quick Installation, only takes minutes to install

0 – 10 volt dimming ready.

High efficacy, 135 Lumens per watt

50,000 hours rated

5 year warranty

UL & DLC Listed

Suitable for dry and damp environments

Available in Retrofit Troffer Kit

Application:

Indoor general/ambient illumination. Idea for offices, schools, retail, and other architectural spaces that demand energy demand reduction and high quality light.



ZY-T7

Optics:

Volumetric effect achieved by delivering a comfortable mix of light to working and surrounding surfaces, creating balanced illumination throughout the environment.



Technical Data

Color Temperature	2700K to 5000K	Input Voltage	100-277VAC
Beam Angle	120 degrees		
Color Consistency	4 steps	Frequency	50-60Hz
CRI	More than 80	Power Factor	More than 0.99
Operation Temperature	-30-40C	Rated Life	50000hours
Efficiency	More than 135 LPW	Led Type	SMT 2835
UL Listed, DLC QPL Listed		Housing	Aluminum/PC

Product Specification

Product Number	Wattage	Color	Voltage	Lumens	Type	CRI
ZY-T4-25W XNZ	25	3000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XNZ	25	3500K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XNZ	25	4000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XNZ	25	5000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XDZ	25	3000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XDZ	25	3500K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XDZ	25	4000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-25W XDZ	25	5000K	AC 100-277V or AC 100-382V	3300	2x2 Troffer	80
ZY-T4-36W XNZ	36	3000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XNZ	36	3500K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XNZ	36	4000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XNZ	36	5000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XDZ	36	3000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XDZ	36	3500K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XDZ	36	4000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T4-36W XDZ	36	5000K	AC 100-277V or AC 100-382V	5000	2x2 Troffer	80
ZY-T7-36W XNZ	36	3000K	AC100-277V or AC100-382V	5000	2x4 Troffer	80
ZY-T7-36W XNZ	36	3500K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-36W XNZ	36	4000K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-36W XNZ	36	5000K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-36W XDZ	36	3000K	AC100-277V or AC100-382V	5000	2x4 Troffer	80
ZY-T7-36W XDZ	36	3500K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-36W XDZ	36	4000K	AC100-277V or AC100-382V	5000	2x4 Troffer	80
ZY-T7-36W XDZ	36	5000K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-45W XNZ	45	3000K	AC 100-277V or AC 100-382V	5600	2x4 Troffer	80
ZY-T7-45W XNZ	45	3500K	AC 100-277V or AC 100-382V	6000	2x4 Troffer	80
ZY-T7-45W XNZ	45	4000K	AC100-277V or AC100-382V	6000	2x4 Troffer	80
ZY-T7-45W XNZ	45	5000K	AC 100-277V or AC 100-382V	6000	2x4 Troffer	80
ZY-T7-45W XDZ	45	3000K	AC 100-277V or AC 100-382V	5000	2x4 Troffer	80
ZY-T7-45W XDZ	45	3500K	AC 100-277V or AC 100-382V	6000	2x4 Troffer	80
ZY-T7-45W XDZ	45	4000K	AC 100-277V or AC 100-382V	6000	2x4 Troffer	80
ZY-T7-45W XDZ	45	5000K	AC 100-277V or AC 100-382V	6000	2x4 Troffer	80
ZY-T7-50W XNZ	50	3000K	AC 100-277V or AC 100-382V	6250	2x4 Troffer	80
ZY-T7-50W XNZ	50	3500K	AC100-277V or AC100-382V	6250	2x4 Troffer	80
ZY-T7-50W XNZ	50	4000K	AC 100-277V or AC 100-382V	6350	2x4 Troffer	80
ZY-T7-50W XNZ	50	5000K	AC 100-277V or AC 100-382V	6350	2x4 Troffer	80
ZY-T7-50W XDZ	50	3000K	AC 100-277V or AC 100-382V	6250	2x4 Troffer	80
ZY-T7-50W XDZ	50	3500K	AC100-277V or AC100-382V	6350	2x4 Troffer	80
ZY-T7-50W XDZ	50	4000K	AC 100-277V or AC 100-382V	6350	2x4 Troffer	80
ZY-T7-50W XDZ	50	5000K	AC 100-277V or AC 100-382V	6350	2x4 Troffer	80

Warranty

This product has a warranty of period of 5 years from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering or removal of the Q.C. and/or date label, usage in improper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to correct installation and return of the faulty unit. Manufacturer does not accept responsibility for any installation costs associated with the replacement of this product. This warranty is in addition to the statutory rights in your country of purchase. Manufacturer reserves the right to alter specifications without prior notice. Please contact DigiLite LED for further information.