

SPECIFIER'S GUIDE + TECHNICAL DATA



	APPLICATION	WIDTH(S)	THICKNESS	PROFILE	SPECIFY AS
SOLID WOOD	Thinclad	4" Face Width	3/8" Solid	Tongue and Groove	Blackboard Pine/ SGPTC-040-BP
	Cladding	4" Face Width	5/8" Solid	Tongue and Groove	Blackboard Pine/ SGPCL-040-BP
	Custom widths & profiles are available. Custom factory stains and finishes available on all products.				Inquire to build your custom specification

PROFILE DETAILS / Note: drawings are not to scale,

T&G: MICRO-BEVEL

Standard on most engineered products, recommended for most prefinished items & wall cladding

۲ ۲ -

T&G: THINCLAD WITH MICRO-BEVEL

Recommended for interior wall cladding

DESCRIPTION

Reclaimed Solid Pine (Southern Yellow Pine)

MILLWORK

Surfaced 4 sides with profile as per specification.

DIMENSIONS

THINCLAD CLADDING:

3/8" thick x 4" wide x 2' to 12' solid random lengths (or longer).

CLADDING:

5%" thick x 4" wide x 2' to 12' solid random lengths (or longer).

SPECIES

Pinus, or occasionally others.

HARDNESS

Janka rating 460

SUSTAINABILITY

Post-consumer reclaimed from sources including highschool and college gymnasium bleachers throughout the U.S. May qualify for LEED MR 4.1 or MR 4.2 (recycled content), EQ 4.2 (Low- Emitting Materials).

LEAD TIME

Typically 4-6 weeks depending on inventory.

CHARACTER/GRADE

Clear and clean, mixed grain with regularly-occuring bolt holes. Holes are pluged with 3/4" diameter reclaimed Grandstand Pine plugs.

FLAME SPREAD USDA FSI Pine: 195 (class C)

PRODUCT SUITE

Interior Cladding, Tables, Benches and custom applications. Inquire for details.

MINIMUM ORDER 250 square feet

Note: Wood is a natural substance and varies in appearance. Please refer to product images or request samples for a broader representation of the color and character of your selection.